



2040-07

Aluminum Frame Self-Luminous Exit Sign

| | |
|----------|-----------|
| DATE: | COMMENTS: |
| PROJECT: | |

FEATURES

- Requires no electricity, lamp, batteries, or external light source making this maintenance free.
- Designed to be tamper-proof.
- No electronics or wiring is required resulting in easy installations.
- Suitable for use in damp, wet, hazardous, or extreme temperature locations.
- Custom wording and pictograms are available upon request. Consult factory for more details.
- 10 or 20 year service life options are available.



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS
Only available with Adobe Acrobat and Acrobat Reader

ORDERING INFORMATION 2040-07-10-2-BK-BA-MTE

| 1. SERIES | 2. SERVICE LIFE | 3. FACE COUNT | 4. FACE COLOR | 5. FRAME COLOR | 6. MOUNTING | 7. OPTIONS |
|-----------|--------------------------|---------------|---|--|---|---|
| 2040-07 | - | 2 | - | - | - | - |
| | 10 10 Year 20 20 Year | 2 Double | BK Black G Green R Red BZ Bronze | BA Brushed Aluminum BK Black WH White BZ Bronze | MTE Top/End Mount MPA 12" Pendant Mount MPB 24" Pendant Mount MPC 36" Pendant Mount MPD 48" Pendant Mount | BLANK = NO OPTION CW Custom Wording VR 1/8" Vandal Resistant Lens |

ACCESSORIES; ORDER SEPARATELY

- WG-16.5LX14.0WX3.0D = Wireguard, Length: 16.5", Width: 14", Depth: 3"
- WG-16.5LX14.0WX6.0D = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- WG-20.0LX19.0WX9.0D = Wireguard, Length: 20", Width: 19", Depth: 9"
- WG-26.0LX19.0WX9.0D = Wireguard, Length: 26", Width: 19", Depth: 9"

SPECIFICATIONS

CONSTRUCTION

- Extruded aluminum frame and painted stencil.

LETTERS

- 6" high; 0.75" stroke

ARROWS

- Universal chevrons

VIEWING DISTANCE

- 100 foot visibility rating

TECHNOLOGY

- Isolite Self-Luminous Signs are illuminated with a light source that consists of glass tubes which are internally coated with phosphor and filled with tritium gas, a natural hydrogen isotope.

WEIGHT

- Double Face: 8 lbs
- Single Face: See the 2040-01

TEMPERATURE RATING

- From -67°F to 176°F

APPROVALS

- UL Listed to standard UL 924 & CAN/ULC-S572
- NFPA 101 Life Safety Code
- NEC Article 500, Class I, II, and III conditions

WARRANTY

- Our self-luminous products are warranted against any defects in material or workmanship for the rated life of the product. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

