



2040-95

Vandal Resistant Aluminum Self-Luminous Exit Sign

DATE:

PROJECT:

COMMENTS:

FEATURES

- Rugged, full-enclosure acrylic cover snaps permanently over frame with no visible fasteners.
- Requires no electricity, external light source, lamps, batteries, or wires resulting in easy install and no maintenance.
- Approved for floor proximity or above-door applications.
- Approved for use in damp, wet, hazardous, and extreme temperature locations.
- 10 or 20 year service life options are available.



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS

Only available with Adobe Acrobat and Acrobat Reader

ORDERING INFORMATION 2040-95-10-1-BK-MB

1. SERIES	2. SERVICE LIFE	3. FACE COUNT	4. FACE COLOR	5. FRAME COLOR	6. MOUNTING
2040-95	-	-	-	-	-
	10 10 Years 20 20 Years	1 Single 2 Double	BK Black G Green R Red BZ Bronze	BA Brushed Aluminum BK Black WH White BZ Bronze	MB Surface Wall Mount ¹ ME End Mount / Side Mount MPA 12" Pendant Mount MPB 24" Pendant Mount MPC 36" Pendant Mount MPD 48" Pendant Mount MT Top Mount

ORDERING NOTES

1. MB is only available on single faced signs.

ACCESSORIES; ORDER SEPARATELY

- **WG-16.5LX14.0WX3.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 3"
- **WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- **WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- **WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

SPECIFICATIONS

FRAME CONSTRUCTION

- Extruded aluminum frame mounted in molded ABS protective enclosure.
- Painted aluminum stencil

LETTERS

- 6" high; 0.75" stroke

ARROWS

- Universal chevrons

VIEWING DISTANCE

- 100 foot visibility rating

TECHNOLOGY

- Isolite Self-Luminous Signs are illuminated with a light source that consists of glass tubes which are internally coated with phosphor and filled with tritium gas, a natural hydrogen isotope.

WEIGHT

- Single Face: 3.5 lbs
- Double Face: 7.2 lbs

TEMPERATURE RATING

- From -67°F to 176°F

APPROVALS

- UL Listed to standard UL 924 & CAN/ULC-S572
- NFPA 101 Life Safety Code
- NEC Article 500, Class I, II, and III conditions

WARRANTY

- Our self-luminous products are warranted against any defects in material or workmanship for the rated life of the product. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

