



CLP

Chicago Approved LED Exit Sign

DATE:

PROJECT

COMMENTS:

FEATURES

- Approved in the City of Chicago.
- Attractive, contemporary steel housing design that is UL listed for use in damp locations.
- White LEDs offer great energy efficiency with high output.
- Charge rate/power ON LED indicator light, and push to test switch for mandated code compliance testing.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 2 hour emergency illumination.
- Available in single or double face configurations.
- Maintenance free nickel cadmium batteries are rechargeable and offer a long product life.
- 120/277 VAC with field selectable inputs.



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS

Only available with Adobe Acrobat and Acrobat Reader

ORDERING INFORMATION *CLP-AC-R-CHI2-BK-MTEB*

1. SERIES

CLP

2. OPERATIONS

AC AC Only
EM Ni-Cad Battery Backup

3. ILLUMINATION

R

R Red

4. FACE COUNT

CHI2 Single Face Stairs No Arrow
 CHI3 Single Face Exit No Arrow
 CHI5 Single Face Stairs Right Arrow
 CHI6 Single Face Exit Right Arrow
 CHI8 Single Face Stairs Left Arrow
 CHI9 Single Face Exit Left Arrow
 CHI12 Single Face Exit Double Arrow
 CHI17 Double Face Stairs No Arrow
 CHI18 Double Face Exit No Arrow
 CHI20 Double Face Stairs Right or Left Arrow
 CHI21 Double Face Exit Right or Left Arrow
 CHI23 Double Face Stairs Double Arrow
 CHI24 Double Face Exit Double Arrow

5. FRAME COLOR

BK Black
WH White

6. MOUNTING

MTEB

MTEB Top/End/Back Mount

ACCESSORIES; ORDER SEPARATELY

- **WG-16.5LX14.0WX3.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 3"
- **WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- **WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- **WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

SPECIFICATIONS

CONSTRUCTION

- Durable, 20-gauge steel
- Neutral powder coated white finish

MOUNTING

- Side and back knockouts are provided for mounting convenience.
- Canopy is provided for universal (top, end, or back) mounting.

LETTERS

- 6" high; 0.75" stroke

ARROWS

- Chicago Approved Arrows

WEIGHT

- AC: 7.5 lb
- EM: 8 lb

TEMPERATURE RATING

- From 32°F to 122°F

APPROVALS

- City of Chicago Approved
- CEC Title 20 Compliant
- UL 924
- UL Listed for Damp Location
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA
- NAFTA

WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

