



EUG

Universal Surface Mount Edge-Lit LED Exit Sign

DATE: []	COMMENTS: []
PROJECT []	[]

FEATURES

- Super-bright LEDs with long life expectancy.
- Suitable for damp locations.
- Unique pivoting housing suitable for ceiling, wall, or end mount applications.
- The energy consumption is less than 2 watts of nominal power.
- Charge rate/power "ON" LED indicator light and push-to-test switch are provided for mandated code compliance testing.
- Maintenance free nickel cadmium batteries with long life expectancy.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Full automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours while reducing overcharge and improving the life of the battery.
- Brownout detection ensures emergency operation during periods of low line voltage.
- 120/277 VAC with field selectable inputs.



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS

Only available with Adobe Acrobat and Acrobat Reader

ORDERING INFORMATION *EUG-AC-G-1C-MTEB*

1. SERIES	2. OPERATION TYPE	3. ILLUMINATION	4. FACE COUNT	5. MOUNTING
EUG	-	-	-	MTEB
	AC AC Only EM Ni-Cad Battery Backup	G Green R Red	1C Single Face, Clear Background 2M Double Face, Mirror Background	MTEB Top/End/Back Mount

ACCESSORIES; ORDER SEPARATELY

- **EUNR1M** = Conversion Panel, Single Face, Red Letters, Mirror Background
- **EUNG1M** = Conversion Panel, Single Face, Green Letters, Mirror Background
- **EUNR2M** = Conversion Panel, Double Face, Red Letters, Mirror Background
- **EUNG2M** = Conversion Panel, Double Face, Green Letters, Mirror Background
- **PKIT1-WH-12** = 12" Swivel Mounting Pendant Kit, White
- **PKIT1-WH-24** = 24" Swivel Mounting Pendant Kit, White
- **PKIT1-WH-36** = 36" Swivel Mounting Pendant Kit, White
- **PKIT1-WH-48** = 48" Swivel Mounting Pendant Kit, White
- **PKIT1-BK-12** = 12" Swivel Mounting Pendant Kit, Black
- **PKIT1-BK-24** = 24" Swivel Mounting Pendant Kit, Black
- **PKIT1-BK-36** = 36" Swivel Mounting Pendant Kit, Black
- **PKIT1-BK-48** = 48" Swivel Mounting Pendant Kit, Black
- **WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- **WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- **WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

SPECIFICATIONS
CONSTRUCTION

- Attractive, low profile satin extruded aluminum with matching gray end-caps.
- Clear acrylic, edge-lit lens is provided for single faced signs while mirrored background is standard for double faced signs.

ARROWS

- NFPA-type, universal field installable, self-adhesive chevrons.

LETTERS

- 6" high; 0.75" stroke

TEMPERATURE RATING

- From 50°F to 104°F

APPROVALS

- UL 924
- CEC Title 20 Compliant
- NFPA 101 Life Safety Code
- NEC NFPA 70
- OSHA

WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS
