



LP-CTMA

Steel Connecticut & Massachusetts Compliant LED Mobility Exit Sign

DATE:	COMMENTS:
PROJECT:	

FEATURES

- Complies with the State of Connecticut Building Code requirements, and provides an exit sign with a 6.0" International Symbol of Accessibility.
- Universal mounting pattern stamped into the back plate for easy surface mounting to a j-box.
- Long life, maintenance-free nickel cadmium battery provides the required 90 minutes of emergency operation.
- Electronic control circuit and isolation transformer provide current control and circuit protection, ensuring optimum LED efficiency and life.
- Solid-state transfer relay ensures the relay contacts do not oxidize or fail resulting in high reliability.
- Energy efficient LEDs with high output.
- Line-latch prevents unnecessary discharge of battery during installation. Loads will not illuminate until after application of utility power.
- Brownout detection ensures emergency operation during periods of low line voltage.
- LED AC present indicator and push-to-test switch are provided standardly.
- 120/277 VAC with field selectable inputs.



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS
Only available with Adobe Acrobat and Acrobat Reader

SYMBOL KEY



DSA = Dynamic Symbol of Accessibility (CT)



ISA = International Symbol of Accessibility (MA)

ORDERING INFORMATION *LP-CTMA-AC-G-1-DSA-WH-MB*

1. SERIES	2. BATTERY	3. ILLUMINATION	4. FACE COUNT	4. SYMBOL
LP-CTMA	-	-	-	-
	AC AC Only EM Ni-Cad Battery Backup	G Green R Red	1 Single 2 Double U Universal	DSA Dynamic Symbol of Accessibility (CT) ISA International Symbol of Accessibility (MA)
6. FRAME COLOR	7. MOUNTING	8. OPTIONS		
WH White BK Black	MTEBP Universal Mount MPAB 12" Swivel Mount (Black) MPAW 12" Swivel Mount (White)	BLANK = NO OPTION AA Audible Alarm (Buzzer) FL Flasher		

ACCESSORIES; ORDER SEPARATELY

- WG-20.0LX19.0WX9.0D = Wireguard, Length: 20", Width: 19", Depth: 9"
- WG-26.0LX19.0WX9.0D = Wireguard, Length: 26", Width: 19", Depth: 9"



SPECIFICATIONS

CONSTRUCTION

- Durable, 20 gauge steel

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- NFPA-type, universal field selectable chevrons.

WEIGHT

- AC: 5.4 lbs
- EM: 5.7 lbs

TEMPERATURE RATING

- From 50°F to 113°F

APPROVALS

- CSA-US listed
- Meets or exceeds UL 924 standards
- State of Connecticut Building Code Paragraph 1011.1.2
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA
- BAA Compliant

WARRANTY

Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.

DIMENSIONS

