



PH100

Photoluminescent Exit Sign

DATE:

PROJECT:

COMMENTS:

FEATURES

- Activation requires only 5 foot-candles (54 lux) of unfiltered fluorescent or LED light for 60 minutes (must be externally illuminated during normal building occupation).
- The photoluminescent material allows for a 100' viewing distance.
- Suitable for use in indoor, outdoor, wet, and hazardous locations.
- The life expectancy is 25+ years.
- Universal, field installed chevrons are universal and field installable.
- No electrical connections are needed for operation.
- Installation is fast, easy, and maintenance free.



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS
Only available with Adobe Acrobat and Acrobat Reader

ORDERING INFORMATION PH100-1-BK-MTEB

1. SERIES

PH100

2. FACE COUNT

- 1 Single
- 2 Double

3. FACE COLOR

- BK Black
- G Green
- R Red

4. MOUNTING

MTEB

MTEB Top/End/Back Mount

ACCESSORIES; ORDER SEPARATELY

- WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

SPECIFICATIONS

CONSTRUCTION

- Durable ABS background panel is available in red, green, or black, with standard photoluminescent letters.

APPROVALS

- UL 924
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA

WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

