

DATE:	COMMENTS:
<input type="text"/>	<input type="text"/>
PROJECT:	
<input type="text"/>	

## FEATURES

- UL listed for use in wet locations.
- Red or green ultra-bright, energy efficient, long life LEDs can be used for the lettering.
- Supports high performance, ultra bright, premium grade MVH lamp heads. Each emergency lamp totals 1.17W.
- Remote capacity and self diagnostics are standard and integral to this unit.
- Will operate two single head remotes or one double head remote with a maximum load of 3W.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- Utilizes 3.6V rechargeable maintenance free nickel cadmium batteries.
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- 120/277 VAC with field selectable inputs.



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS  
Only available with Adobe Acrobat and Acrobat Reader

## ORDERING INFORMATION *RWL-C-G-U-WH-MEB-SD-EB*

**RWL-C-G-U-WH-MEB-SD-EB** RWL-C Wet Location Thermoplastic LED Exit Sign, Green Legend  
**RWL-C-R-U-WH-MEB-SD-EB** RWL-C Wet Location Thermoplastic LED Exit Sign, Red Legend

## ACCESSORIES; ORDER SEPARATELY

- **WG-16.5LX14.0WX3.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 3"
- **WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- **WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- **WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

## SPECIFICATIONS

### CONSTRUCTION

- Polycarbonate faceplate provides UV resistance.
- Integrated gasket ensures internal protection.
- Thermoplastic housing creates a high impact, corrosion resistant exterior.

### ARROWS

- Field selectable knockout chevron directional indicators

### TEMPERATURE RATING

- From 32°F to 122°F

### APPROVALS

- UL 924
- UL 924 Wet Location
- CEC Title 20 Compliant
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA

### WARRANTY

- Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.

**DIMENSIONS**

