



# RWL

Wet Location Thermoplastic LED Exit Sign

DATE:	COMMENTS:
PROJECT:	

## FEATURES

- Suitable for wet location applications.
- Super-bright LEDs with long life expectancy.
- Quick-connect components and snap-on canopy for easy installation.
- Nickel cadmium battery provides a minimum of 90 minute emergency operation.
- Sealed external momentary test switch and dual diagnostic LED indicator displays AC presence and Hi-Charge status.
- Self-Test / Self-Diagnostic monitoring is available.
- Low voltage cut-off prevents battery damage and ensures positive charge acceptance following an extended discharge.
- Line-latch prevents unnecessary discharge of battery during installation. Loads will not illuminate until after application of utility power.
- 120/277 VAC with field selectable inputs (with the exception of the C1/C2 (dual circuit) option which requires voltage specification upon ordering).



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS  
Only available with Adobe Acrobat and Acrobat Reader

## ORDERING INFORMATION *RWL-AC-G-1-BK-MTEBP*

1. SERIES	2. OPERATION	3. ILLUMINATION	4. FACE COUNT	5. FRAME COLOR
<b>RWL</b>	- -	-	-	-
	<b>AC</b> AC Only <b>EM</b> Ni-Cad Battery Backup	<b>G</b> Green <b>R</b> Red	<b>1</b> Single <b>2</b> Double	<b>BK</b> Black <b>GY</b> Gray <b>WH</b> White
6. MOUNTING	7. OPTIONS			
<b>MTEBP</b>	-			
<b>MTEBP</b> Universal Mount	<b>BLANK = NO OPTION</b> <b>C1</b> Dual Circuit - 120 VAC (AC Only) <sup>1</sup> <b>C2</b> Dual Circuit - 277 VAC (AC Only) <sup>1</sup>	<b>SD</b> Self-Diagnostics (EM Only) <b>TP</b> Tamperproof Screws		

## ORDERING NOTES

- This dual circuit option should only be used for exits which are intended to be connected simultaneously to normal and emergency power circuits, but cannot support two hot inputs. Only one of the normal or emergency circuits can be powered at any given time. Energizing both normal and emergency circuits simultaneously will result in damage to the exit sign.

## ACCESSORIES; ORDER SEPARATELY

- **WG-16.5LX14.0WX3.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 3"
- **WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- **WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- **WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

**SPECIFICATIONS**
**CONSTRUCTION**

- 5VA flame retardant
- UV Stabilized Polycarbonate housing
- High-impact resistant polycarbonate lens
- Corrosion resistant enclosure
- Knockouts provided for conduit feed applications

**LETTERS**

- 6.0" high; 0.75" stroke

**ARROWS**

- NFPA-type, field selectable chevrons.

**TEMPERATURE RATING**

- From -4°F to 122°F

**ELECTRICAL**

- Input Power: 3.4W Max

**APPROVALS**

- UL 924 Listed for Wet Location
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA
- CEC Title 20 Compliant

**WARRANTY**

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

**DIMENSIONS**
