

*Click the Product You Wish to View on [Isolite.com](https://www.isolite.com)

EXITS & COMBOS	GOOD	BETTER	BEST
Thermoplastic Exit / Combo	 RL Reliance Series Thermoplastic LED Exit Sign No Remote Capacity	 CMB Thermoplastic LED Exit Sign & Emergency Combo Remote Capacity	 RLC-LED Thermoplastic Exit & Emergency Combo Remote Capacity, Lamps Removable
Material	Thermoplastic	Thermoplastic	Thermoplastic
Temperature Range	From 32°F to 122°F	From 32°F to 122°F	From 50°F to 104°F
Ratings	- UL 924 - CEC Title 20 Compliant - UL Listed for Damp Location - NFPA Life Safety Code 101 - NFPA 70-NEC - OSHA	- UL 924 - NFPA Life Safety Code 101 - NFPA 70-NEC - OSHA - Damp Location Listed - CEC Title 20 Compliant	- UL 924 - UL Listed for Damp Location - NFPA Life Safety Code 101 - NFPA 70-NEC - OSHA
Aluminum Exit	 EDC Economical Die-Cast LED Exit Sign	 LPDC2 Die-Cast Aluminum Exit Sign	 TL2.0 Thin Line Die-Cast LED Exit Sign CEC
Material	Die-Cast Aluminum	Die-Cast Aluminum	Die-Cast Aluminum
Temperature Range	From 32°F to 122°F	From 50°F to 104°F	From 50°F to 104°F
Ratings	- UL 924 - UL Listed for Damp Location - CEC Title 20 Compliant - NFPA Life Safety Code 101 - NFPA 70-NEC - OSHA	- UL 924 - NEMA 4X (See Wet Location Fixture) - CEC Title 20 Compliant - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - BAA Compliant	- UL 924 - CEC Title 20 Compliant - UL 924 Damp Location - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - Assembled in the USA
Edge-Lit Exit	 EUG Universal Surface Mount Edge-Lit LED Exit Sign	 UEL Universal Recessed Edge-Lit LED Exit Sign	 ELT2 Edge-Lit LED Exit Sign
Material	Extruded Aluminum & Acrylic Lens	Extruded Aluminum with Steel Recessed Backbox & Acrylic Lens	Precision die-cast aluminum housing with a flawless, laser-formed acrylic legend
Temperature Range	From 50°F to 104°F	From 50°F to 104°F	From 32°F to 102°F
Ratings	- UL 924 - UL Listed for Damp Location - CEC Title 20 Compliant - NFPA 101 Life Safety Code - NEC NFPA 70 - OSHA	- UL 924 - UL Listed for Damp Location - CEC Title 20 Compliant - NFPA 101 Life Safety Code - NEC - OSHA	- UL 924 - CEC Title 20 Compliant - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - Recessed Backbox is IC Rated & Meets New York City & Chicago Specifications - FCC Title 47 Part 15, Subpart B - Assembled in the USA
Wet Location Exit	 RWL Wet Location Thermoplastic LED Exit Sign	 LPDC2-LW Wet Location Die-Cast Aluminum Exit Sign	 HLX NEMA 4X LED Exit Sign
Material	UV Stabilized Polycarbonate Housing with Stainless Steel Captive Screws to Secure Lens Cover to Housing	Injection-Molded Internal Cavity Reflector & Heavy-Duty Pressure Die-Cast Aluminum Alloy	Corrosion Resistant ABS Thermoplastic Housing & Fully Gasketed with Hot Bonded Silicone
Temperature Range	From -4°F to 122°F	- Standard: 50°F to 104°F - With HX Option: -40°F to 104°F	- Without Internal Heater: From 50°F to 104°F - With Internal Heater: From -4°F to 104°F
Ratings	- UL 924 Listed for Wet Location - NFPA Life Safety Code 101 - NFPA 70-NEC - OSHA - NEMA 4X	- UL 924 Listed to 100ft Visibility Distance - CEC Title 20 Compliant - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - NEMA 4X - BAA Compliant	- CSA-US Listed - CEC Title 20 Compliant - IP44 - ETL Sanitation Listed - Meets or exceeds UL 924 standards - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - BAA Compliant - NEMA 4X

*Click the Product You Wish to View on Isolite.com

EXITS & COMBOS CONTINUED

	GOOD	BETTER	BEST
Wet Location Combo	 RWL-C Wet Location Thermoplastic LED Exit Sign	 MAX-C Wet Location Die-Cast Exit & Emergency Combo	 HLX-C NEMA 4X Exit & Emergency Combo
Material	UV Resistant Polycarbonate Faceplate with High Impact Corrosion Resistant Thermoplastic	Heavy-Duty 0.420" Cast Aluminum Lamp Housing Constructed of Vandal Resistant Polycarbonate	Corrosion Resistant, ABS Thermoplastic, Fully Gasketed with Hot Bonded Silicone
Temperature Range	From 32°F to 122°F	From 50°F to 104°F	- Without Internal Heater: From 50°F to 104°F - With Internal Heater: From -4°F to 104°F
Ratings	- UL 924 - UL 924 Wet Location - NFPA Life Safety Code 101 - NFPA 70-NEC - OSHA	- CSA-US listed - Meets or exceeds UL 924 standards - IP66 - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - BAA Compliant - NEMA 4X	- Intertek Verified Splash Zone - CSA-US listed - UL 924 - IP44 - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - BAA Compliant - NEMA 4X
Photoluminescent Exit	 PHL Thermoplastic Photoluminescent Exit Sign	 PH Aluminum Frame Photoluminescent Exit Sign	 PH100 Photoluminescent Exit Sign
Material	Thermoplastic Frame with Strontium Oxide Aluminate Photoluminescent Pigment Molded Into a Rigid Fire/Flame-Resistant PVC Sheet	Extruded Aluminum Frame With Strontium Oxide Aluminate Photoluminescent Pigment Molded Into a Rigid Flame/Fire-Resistant PVC Sheet	Durable ABS Background Panel Available in Red, Green, or Black, with Photoluminescent Letters
Temperature Range	Non-Electrical	Non-Electrical	Non-Electrical
Ratings	50 Ft. Viewing - UL 924 - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA	50 Ft. Viewing - UL 924 - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA	100 Ft. Viewing - UL 924 - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA
Self-Luminous Exit	 SLX-60 ABS Plastic Frame Self-Luminous Exit Sign	 2040-01 Aluminum Frame Self-Luminous Exit Sign	 880 Thinline Aluminum Self-Luminous Exit Sign
Material	Flame Retardant, UV Stabilized, Injection Molded ABS Frame	Extruded Aluminum Frame with Painted Extruded Aluminum Stencil	Extruded Aluminum Frame with Painted Extruded Aluminum Stencil
Temperature Range	From -67°F to 176°F	From -67°F to 176°F	From -67°F to 176°F
Ratings	- UL Listed to standard UL 924 & CAN/ULC-S572 - NFPA 101 Life Safety Code - NEC Article 500, Class 1, 11, & 111 Conditions 10 or 20 Year Options Available	- UL Listed to standard UL 924 & CAN/ULC-S572 - NFPA 101 Life Safety Code - NEC Article 500, Class 1, 11, & 111 Conditions 10 or 20 Year Options Available	- UL Listed to standard UL 924 & CAN/ULC-S572 - NFPA 101 Life Safety Code - NEC Article 500, Class 1, 11, & 111 Conditions 10 or 20 Year Options Available
Vandal Resistant (VR) Self-Luminous Exit	 SLX-60 (VR) ABS Plastic Frame Self-Luminous Exit Sign	 2040-95 Vandal Resistant Self-Luminous Exit Sign	 2040-70 Vandal Proof Institutional Self-Luminous Exit Sign
Material	Flame Retardant, UV Stabilized, Injection Molded ABS Frame with VR Shield	Extruded Aluminum Frame Mounted in Molded ABS Protective Enclosure with Painted Aluminum Stencil	Cast Aluminum Frame, 0.187" Thick, Extends from Faceplate At 45° Angle from the Wall
Temperature Range	From -67°F to 176°F	From -67°F to 176°F	From -67°F to 176°F
Ratings	- UL Listed to standard UL 924 & CAN/ULC-S572 - NFPA 101 Life Safety Code - NEC Article 500, Class 1, 11, & 111 Conditions 10 or 20 Year Options Available	- UL Listed to standard UL 924 & CAN/ULC-S572 - NFPA 101 Life Safety Code - NEC Article 500, Class 1, 11, & 111 Conditions 10 or 20 Year Options Available	- UL Listed to standard UL 924 & CAN/ULC-S572 - NFPA 101 Life Safety Code - NEC Article 500, Class 1, 11, & 111 Conditions 10 or 20 Year Options Available

*Click the Product You Wish to View on Isolite.com

EXITS & COMBOS CONTINUED	GOOD	BETTER	BEST
Chicago Exits		 CLP Chicago Approved LED Exit Sign	 PG Chicago Approved LED Edge-Lit Exit Sign
Material		Durable 20-Gauge Steel	Precision, Die-Cast Aluminum Housing with Laser Formed Acrylic Legend
Temperature Range		From 32°F to 122°F	From 50°F to 104°F
Ratings		- City of Chicago Approved - CEC Title 20 Compliant - UL 924 - UL Listed for Damp Location - NFPA Life Safety Code 101 - NFPA 70-NEC - OSHA - NAFTA	- City of Chicago Approved - UL 924 - NFPA Life Safety Code 101 - NFPA 70-NEC - OSHA - NAFTA - Optional Damp Location Listing - Assembled in the USA
New York City Exits	 EDC-NYC NYC Approved Economical Die-Cast LED Exit Sign	 UEL with R8 Universal Recessed Edge-Lit LED Exit Sign	 ELT2 with R8 Edge-Lit LED Exit Sign
Material	Premium-Grade, Aluminum Housing	Low Profile Satin Extruded Aluminum	Precision Die-Cast Aluminum Housing with a Flawless, Laser-Formed Acrylic Legend
Temperature Range	From 32°F to 122°F	From 50°F to 104°F	From 32°F to 102°F
Ratings	- New York City Approved - UL Listed for Damp Location - UL 924 - NFPA Life Safety Code 101 - NFPA 70-NEC - OSHA	- New York City Approved - UL 924 - CEC Title 20 Compliant - NFPA 101 Life Safety Code - NEC - OSHA	- UL 924 - CEC Title 20 Compliant - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - Recessed Backbox is IC Rated & Meets New York City & Chicago Specifications - FCC Title 47 Part 15, Subpart B - Assembled in the USA
Mobility Approved Exits Massachusetts & Connecticut	 LP-CTMA Steel Connecticut & Massachusetts Compliant LED Mobility Exit Sign	 LPX-CTMA Connecticut & Massachusetts Aluminum LED Mobility Exit Sign	 ECTMA Connecticut & Massachusetts Compliant Recessed Mobility Exit Sign
Material	Durable 20-Gauge Steel	Durable, Extruded Aluminum	Durable 20-Gauge Steel with White-Baked Powder Coat Finish & High Clarity Acrylic
Temperature Range	From 50°F to 113°F	From 50°F to 113°F	From 50°F to 113°F
Ratings	- CSA-US listed - Meets or exceeds UL 924 standards - State of Connecticut Building Code Paragraph 1011.1.2 - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - NAFTA	- CSA-US listed - UL 924 - State of Connecticut Building Code Paragraph 1011.1.2 - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - NAFTA	- CSA-US listed - Meets or Exceeds UL 924 Standards - State of Connecticut Building Code Paragraph 1011.1.2 - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA
			 EU-CTMA Connecticut & Massachusetts Compliant Indoor Mobility Exit Sign
			Durable 20-Gauge Steel with White-Baked Powder Coat Finish & High Clarity Acrylic
			From 50°F to 113°F
			- CSA-US listed - Meets or Exceeds UL 924 Standards - State of Connecticut Building Code Paragraph 1011.1.2 - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA

*Click the Product You Wish to View on [Isolite.com](https://www.isolite.com)

EXITS & COMBOS CONTINUED

	GOOD	BETTER	BEST
Hazardous & Industrial Exits / Combo	 HZE Class 1 Div 2 LED Exit Sign	 HZC Class 1 Div 2 Exit & Emergency Combo	 EXP Explosion Proof Edge-Lit LED Exit Sign
Material	Durable, Corrosion Resistant, Gray Fiberglass & Fully Gasketed for Harsh & Hazardous Locations. High Clarity, Scratch Resistant, Clear Polycarbonate Face	Fully Gasketed, Die-Cast Aluminum Housing with Impact Resistant Polycarbonate Lens Stainless Steel Mounting Feet & Hardware Industrial Gray Color Standard	Precision Die-Cast Aluminum Housing With A Flawless, Laser-Formed Acrylic Legend
Temperature Range	From 50°F to 104°F	From 50°F to 104°F	From 50°F to 104°F
Ratings	- NEMA 4X - CSA-US Listed - CEC Title 20 Compliant - Class I Div 2 Groups A-D - IP66 - Sanitation Listed - ETL Verified Splash Zone Listing Equal to NSF Standard 2 - Meets or Exceeds UL 924 Standards - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - NAFTA - BAA Compliant	- CSA-US listed - NEMA 4X - Class I Div 2 Groups A-D: T2B area Classification - Class I Zone 2, IIA, IIB & IIC: T1 & T2 Area Classification - Meets or Exceeds UL 924 Standards - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - BAA Compliant	- Class I, Div 1 Groups C & D - Class I, Div 2 Groups A, B, C & D - Class II, Div 1 Groups E, F & G - Class III, Div 1 - Class I, Zone 1, Groups IIA, IIB - Class I, Zone 2, Groups IIA, IIB + H2 & IIC - Temperature Class (T-Rating)-T6 - UL 924 - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA
Custom Graphic Signs	 LPDCCG2 Die-Cast Aluminum Exit Sign, Custom Graphics	 ELTCG2 Edge-Lit LED Exit Sign With Custom Graphics	 TLCG2 Thin Line Die-Cast Custom Graphics LED Exit Sign
Material	Heavy-Duty, Three-Piece Die-Cast Aluminum Housing With A Removable Front Stencil & Light Seal	Precision Die-Cast Aluminum Housing with a Flawless, Laser-Formed Acrylic Legend	Heavy Duty, Two Piece Walls Constructed from Die Cast Aluminum Alloy & Removable Front Stencil Face with Overlapping Light Seal
Temperature Range	From 50°F to 104°F	From 32°F to 102°F	From 50°F to 104°F
Ratings	- UL 924 Listed to 100ft Visibility Distance - CEC Title 20 Compliant - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - NEMA 4X (See Wet Location Fixture) - BAA Compliant	- UL 924 - CEC Title 20 Compliant - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - Recessed Backbox is IC Rated & Meets New York City & Chicago Specifications - FCC Title 47 Part 15, Subpart B - Assembled in the USA	- UL 924 - UL 924 Damp Location - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - Assembled in the USA

EMERGENCY LIGHTING

Thermoplastic	 RL2LED Reliance Series Compact LED Emergency Light	 BUG High Performance LED Emergency Light	 AIR Architectural Indoor LED Emergency Light
Material	UV Stabilized, UL94V-O Flame Retardant, ABS Injection-Molded Thermoplastic	5VA Flame Rated, Injection Molded ABS Thermoplastic Housing	5VA Flame Rated, Injection Molded ABS Thermoplastic Housing
Temperature Range	From 50°F to 104°F	From 50°F to 104°F	From 50°F to 104°F
Lumen Output	125 Lumens per Lamp	300-650 Lumens per Lamp	425-840 Lumens per Lamp
Ratings	- UL 924 - UL Listed for Damp Location - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA	- UL 924 - UL Listed for Damp Location - CEC Title 20 Compliant - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA	- cUL Listed in compliance with UL 924 & Canadian CSA-C22.2 No. 141-15 - Damp Location Listed - CEC Title 20 Compliant - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - BAA Compliant

*Click the Product You Wish to View on [Isolite.com](https://www.isolite.com)

EMERGENCY LIGHTING CONTINUED

	GOOD	BETTER	BEST
Recessed	 GNSD Genie MR16 Fully Recessed Emergency Light	 LMIGN2 LED Compact Fully Recessed Emergency Light	 MIGN2 2nd Mini-Genie Fully Recessed Compact LED Emergency Light
Material	Textured White Powder, Coated Die-Cast Zinc Frame & Door	Textured, White Powder Coated, Die-Cast Zinc Frame & Door	Textured, White Powder Coated, Die-Cast Zinc Frame & Door
Lumen Output	Lamp Option Dependent	561 Lumens	407 Lumens per Lamp
Temperature Range	- LC: From 45°F to 85°F - NC: From 32°F to 102°F	From 32°F to 102°F	From 10°C to 40°C
Ratings	- UL 924 - NYC Approved Calendar #48850 - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - Chicago Approved Plenum Option Available - Optional Damp Location Listing - Assembled in the USA	- UL 924 - New York City Approved Calendar #48850 - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - California Energy Commission (CEC) Title 20 Compliant - Assembled in the USA	- UL 924 - NYC Approved Calendar #48850 - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - California Energy Commission (CEC) Title 20 Compliant - NYC Approved Calendar #48850 - Chicago Approved Plenum Option Available - Optional Damp Location Listing - Assembled in the USA
Industrial	 ELP 50-100 Watt Thermoplastic Emergency Light	 ELH 120-360 Watt Emergency Light	 OLLO Industrial Emergency Light
Material	Injection Molded ABS Housing	20-Gauge Steel Cabinet with Durable White Powder-Coat Finish	Die-Cast Aluminum
Heads	2	0-2	0, 2, or 4
Temperature Range	With Internal Heater: 16°F to 104°F	From 50°F to 113°F	- Standard: 50°F to 104°F - With HX Option: Down to -22°F
Ratings	- UL 924 - UL 924 Damp Location - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA	- CSA-US listed - Meets or exceeds UL 924 standards - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - BAA Compliant	- cUL Listed in compliance with UL 924 & Canadian CSA-C22.2 No. 141-15 - NEMA 4X (with LW option)
	 ELL 12-60 Watt Emergency Light		
	20-Gauge Steel Cabinet with Durable White Powder-Coat Finish		
	0-2		
	From 50°F to 113°F		
	- CSA-US listed - Meets or Exceeds UL 924 Standards - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - BAA Compliant		

*Click the Product You Wish to View on Isolite.com

EMERGENCY LIGHTING CONTINUED

	GOOD	BETTER	BEST
Outdoor Wall Pack	 WXPM Mini Outdoor Emergency Light	 OWL Outdoor Wet Location Emergency Light	 WXP Outdoor Emergency Light
Material	Die-Cast Housing with Polycarbonate Lens	Quality Pressure Die-Cast Aluminum Housing Finished in Durable Polyester Powder Coat	Die-Cast Housing with Polycarbonate Lens
Lumen Output	- AC Mode: 700 Lumens - EM Mode: 270 Lumens - REM Mode: 300 Lumens	- AC Mode: 1530 Lumens - EM Mode: 600 Lumens 3000K CCT	13000 Lumens / 4000K CCT at 100W
Temperature Range	- AC: -4°F to 122°F - EM: 41°F to 122°F - Remote Lamp: -22°F to 122°F	- Without Internal Heater: 32°F to 122°F - With Internal Heater: -13°F to 122°F	-4°F to 122°F
Ratings	- UL Listed to standard UL 924 & CAN/ - ULC-S572 - NFPA 101 Life Safety Code - IP65 - IK08	- UL 924 - NEMA 3R Rated - IP65 Certified - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA	- UL Listed to standard UL 924 & CAN/ - ULC-S572 - NFPA 101 Life Safety Code - IP65 - IK10
Wet-Location / Hazardous Industrial	 HL Architectural Outdoor LED Light	 OLLO Industrial Emergency Light	 HZL Hazardous Location Emergency Light
Material	Fully Gasketed NEMA 4X Rated Fiberglass with Housing Durable Gray Powder-Coat Finish	Die-Cast Aluminum	Fully Gasketed, Die-Cast Aluminum Housing With Impact Resistant Polycarbonate Lens
Heads	0-2	0, 2, or 4	0-2
Temperature Range	- Without Internal Heater: 50°F to 104°F - With Internal Heater: -4°F to 104°F	- Standard: 50°F to 104°F - With HX Option: Down to -22°F	From 50°F to 104°F
Ratings	- NEMA 4X - IP66 - CSA-US Listed - Meets or Exceeds UL 924 Standards - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - BAA Compliant - NEMA 4x, 4, 12, & 13	- cUL Listed in compliance with UL 924 & Canadian CSA-C22.2 No. 141-15 - NEMA 4X (with LW option)	- CSA-US Listed - Class I Div 2 Groups A-D: T2B Area Classification - Class I Zone 2, IIA, IIB & IIC: T1 & T2 Area Classification - Meets or Exceeds UL 924 Standards - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - BAA Compliant
Wet Location / Hazardous Location	 RL2LED with LW Reliance Series Compact LED Emergency Light	 HZN NEMA 4X/IP66 Emergency Light	 HZZ Hazardous Location Emergency Light
Material	UV Stabilized, UL94V-O Flame Retardant, ABS Injection-Molded Thermoplastic	Fully Gasketed, Die-Cast Aluminum Housing with Impact Resistant Polycarbonate Lens	Fully Gasketed, Die-Cast Aluminum Housing with Impact Resistant Polycarbonate Lens
Lumen Output	125 Lumens per Lamp	Lamp Option Dependent	Lamp Option Dependent
Temperature Range	From 50°F to 104°F	- Without Internal Heater: From 50°F to 104°F - With Internal Heater: From -4°F to 104°F	From 50°F to 104°F
Ratings	- UL 924 - UL Listed for Damp Location - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - LW Option: NEMA 4X & IP65 Rated	- NEMA 4X - IP66 - Intertek Verified Splash Zone - CSA-US Listed - Meets or Exceeds UL 924 Standards - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - BAA Compliant	- CSA-US Listed - NEMA 4X - Class I Div 2 Groups A-D - Class II Div 1 & 2 Groups E-G - IP66 - Sanitation Listed - ETL Verified Splash Zone Listing Equal to NSF Standard 2 - Meets or Exceeds UL 924 Standards - NFPA 101 Life Safety Code - NFPA 70-NEC - OSHA - BAA Compliant