
















EXIT SIGNS

 <p>HLX NEMA 4X LED Exit Sign</p> <p>Internal Heater (H1/H2): -4°F (-20°C)</p> <p>Rating: NEMA 4X</p>	 <p>MAX Wet Location Die-Cast Exit Sign</p> <p>Internal Heater (H1/H2): -4°F (-20°C) AC: -20°F (-29°C)</p> <p>Rating: IP66</p>	 <p>MAX2.0 Low Profile Wet Location Die-Cast LED Exit Sign</p> <p>Internal Heater (H1/H2): -4°F (-20°C) AC: -20°F (-29°C)</p> <p>Rating: IP66</p>
 <p>RWL ABS Plastic Frame Self Luminous Exit Sign</p> <p>Minimum Cold Temperature: -4°F (-20°C)</p>	 <p>2040-01 Aluminum Frame Self-Luminous Exit Sign</p> <p>Minimum Cold Temperature: -67°F (-55°C)</p>	 <p>2040-07 Aluminum Frame Self-Luminous Exit Sign</p> <p>Minimum Cold Temperature: -67°F (-55°C)</p>
 <p>2040-70 Vandal Resistant Aluminum Self-Luminous Exit Sign</p> <p>Minimum Cold Temperature: -67°F (-55°C)</p>	 <p>2040-80 Recessed Self-Luminous Exit Sign</p> <p>Minimum Cold Temperature: -67°F (-55°C)</p>	 <p>2040-95 Vandal Resistant Aluminum Self-Luminous Exit Sign</p> <p>Minimum Cold Temperature: -67°F (-55°C)</p>
 <p>880 Thin Line Aluminum Self-Luminous Exit Sign</p> <p>Minimum Cold Temperature: -67°F (-55°C)</p>	 <p>SLX-60 ABS Plastic Frame Self Luminous Exit Sign</p> <p>Minimum Cold Temperature: -67°F (-55°C)</p>	




EXIT & EMERGENCY COMBOS

 <p>HLX-C NEMA 4X Exit & Emergency Combo</p> <p>Internal Heater (H1/H2): -4°F (-20°C)</p> <p>Rating: NEMA 4X</p>



EMERGENCY LIGHTING

 <p>OWL Outdoor Wet Location Emergency Light</p> <p>Internal Heater (HX): -13°F (-25°C)</p> <p>Rating: NEMA 3R & IP65</p>	 <p>ELED Architectural Outdoor LED Light</p> <p>Internal Heater (HX): -4°F (-20°C)</p> <p>Rating: IP65</p>	 <p>EL16 MR16 Emergency Light</p> <p>Internal Heater (HX): -4°F (-20°C)</p> <p>Rating: Damp or Wet Location</p>
--	--	---

EMERGENCY LIGHTING (CONTINUED)

 <p>ODLE LED Outdoor Egress Emergency Light</p>	 <p>HL NEMA 4X 18-360 Watt Emergency Light</p>	 <p>HZN NEMA 4X/IP66 Emergency Light</p>
<p>Internal Heater (HX): -4°F (-20°C)</p>	<p>Internal Heater (H1/H2): -4°F (-20°C)</p>	<p>Internal Heater (H1/H2): -4°F (-20°C)</p>
<p>Rating: NEMA 4X & IP66</p>	<p>Rating: NEMA 4X & IP66</p>	<p>Rating: NEMA 4X & IP66</p>

REMOTE LAMP HEADS

 <p>HNS High Output Remote Head</p>	 <p>NRH MR16 Remote Head</p>
<p>Minimum Cold Temperature: -22°F (-30°C)</p>	<p>Minimum Cold Temperature: -22°F (-30°C)</p>
<p>Rating: NEMA 4X & IP66</p>	<p>Rating: NEMA 4X & IP66</p>

ISOLITE CORPORATION TERMS & CONDITIONS

Specifications, pricing and details are subject to change without notification.

[VISIT OUR WEBSITE](#)