

DATE:	COMMENTS:
PROJECT:	



FEATURES

- Rugged, full-enclosure acrylic cover snaps permanently over frame
- Requires no electricity or external light source
- Maintenance free – no lamps or batteries to replace
- Approved for low-level or above-door applications
- Tamper-proof design
- Easy to install – no wiring required
- Ideal for damp, wet, explosion proof, and extreme temperature applications
- Service life – 10 or 20 year options available
- No visible fasteners



ORDERING INFORMATION 2040-95-10-1-BK-MB

1. SERIES	2. SERVICE LIFE	3. FACE COUNT	4. FACE COLOR	5. FRAME COLOR	6. MOUNTING
2040-95	-	-	-	-	-
	10 10 Years 20 20 Years	1 Single 2 Double	BK Black G Green R Red BZ Bronze	BA Brushed Aluminum BK Black WH White BZ Bronze	MB Surface Wall Mount ¹ ME End Mount / Side Mount MPA 12" Pendant Mount MPB 24" Pendant Mount MPC 36" Pendant Mount MPD 48" Pendant Mount MT Top Mount

ORDERING NOTES

1. MB is only available on Single Faced Signs

ACCESSORIES; ORDER SEPERATELY

- WG 2 = Wire guard 14.0" X 10.0" X 4.5"
- WG 3 = Wire guard 14.5" X 6.0" X 10.5"
- WG 10 = Wire guard 13.5" X 12.0" X 16.5"

SPECIFICATIONS

FRAME CONSTRUCTION

- Extruded aluminum frame mounted in molded ABS protective enclosure
- Painted aluminum stencil

LETTERS

- 6" high; 0.75" stroke

ARROWS

- Universal chevrons

VIEWING DISTANCE

- 100 foot visibility rating

DIMENSIONS

TECHNOLOGY

- Isolite Self-Luminous Signs are illuminated with a light source that consists of glass tubes which are internally coated with phosphor and filled with tritium gas, a natural hydrogen isotope

WEIGHT

- Single Face: 3.5 lbs
- Double Face: 7.2 lbs

TEMPERATURE RATING

- From -67°F to 176°F

APPROVALS

- UL Listed to standard UL924 & CAN/ULC-S572
- NFPA 101 Life Safety Code
- NEC Article 500, Class 1, 11, and 111 conditions

WARRANTY

- Our self-luminous products are warranted against any defects in material or workmanship for the rated life of the product. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website

