

DATE:	COMMENTS:
PROJECT:	

FEATURES

- Designed to stand up to abuse in applications such as schools, institutions, public areas and apartment complexes where vandalism may occur
- Requires no electricity or external light source
- Maintenance free – no lamps or batteries to replace
- Beveled-edge, heavy-duty, cast-aluminum frame with unbreakable polycarbonate faceplate
- Available in extruded aluminum, double face design
- Approved for floor proximity or above-door applications
- Easy to install – no wiring required
- Ideal for damp, wet, explosion proof, and extreme temperature applications
- Special wording and pictograms available
- Service life – 10 or 20 year options available
- Custom wording or pictograms available



ORDERING INFORMATION *2040-70-10-1-BK-BA-MB*

1. SERIES	2. SERVICE LIFE	3. FACE COUNT	4. FACE COLOR	5. FRAME COLOR	6. MOUNTING	7. OPTIONS
2040-70	-	-	-	BA	-	-
	10 10 Years 20 20 Years	1 Single 2 Double	BK Black G Green R Red	BA Brushed Aluminum	MB Surface Wall Mount ¹ MT Top Mount / Surface Ceiling	BLANK = NO OPTION CW Custom Wording

ORDERING NOTES

1. Single Face Only

ACCESSORIES; ORDER SEPARATELY

- WG 1 = Wire guard 17.0" X 17.0" X 17.0"

CONSTRUCTION

- Cast aluminum frame, 0.187" thick, extends from faceplate at 45° angle from the wall
- Four holes for #10 tamper-resistant screws
- Aluminum stencil

LETTERS

- 6" high; 0.75" stroke

ARROWS

- Universal chevrons
- Viewing Distance
- 100 foot visibility rating

TECHNOLOGY

- Isolite Self-Luminous Signs are illuminated with a light source that consists of glass tubes which are internally coated with phosphor and filled with tritium gas, a natural hydrogen isotope

WEIGHT

- Single Face: 7 lbs
- Double Face: 26.8 lbs

TEMPERATURE RATING

- From -67°F to 176°F

APPROVALS

- UL Listed to standard UL924 & CAN/ULC-S572
- NFPA 101 Life Safety Code
- NEC Article 500, Class 1, 11, and 111 conditions

WARRANTY

- Our self-luminous products are warranted against any defects in material or workmanship for the rated life of the product. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website

DIMENSIONS

