



2040-80

Recessed Self-Luminous Exit Sign

DATE:

PROJECT:

COMMENTS:

FEATURES

- Requires no electricity or external light source
- Maintenance free – no lamps or batteries to replace
- Approved for floor proximity or above-door applications
- Vandal resistant 3/8" polycarbonate cover
- Tamper-proof design
- Easy to install – no wiring required
- Ideal for damp, wet, explosion proof, and extreme temperature applications
- Custom wording and pictograms available
- Service life – 10 or 20 year options available



ORDERING INFORMATION *2040-80-10-1-BK-BA-MRW*

1. SERIES	2. SERVICE LIFE	3. FACE COUNT	4. FACE COLOR	5. FRAME COLOR	6. MOUNTING	7. OPTIONS
2040-80	-	1	-	-	MRW	-
	10 10 Year 20 20 Year	1 Single	BK Black G Green R Red BZ Bronze	BA Brushed Aluminum BK Black WH White BZ Bronze	MRW Recessed Wall Mount	BLANK = NO OPTION CW Custom Wording

ACCESSORIES; ORDER SEPARATELY

- WG 6 = Wire guard 20.0" X 17.0" X 12.0"

CONSTRUCTION

- Brushed aluminum recessed pan
- Aluminum stencil with 0.375" polycarbonate cover

LETTERS

- 6" high; 0.75" stroke

ARROWS

- Universal chevrons

VIEWING DISTANCE

- 100 foot visibility rating

TECHNOLOGY

- Isolite Self-Luminous Signs are illuminated with a light source that consists of glass tubes which are internally coated with phosphor and filled with tritium gas, a natural hydrogen isotope

ROUGH-IN SIZE

- 12.5625" x 8.25"

WEIGHT

- 6 lbs

TEMPERATURE RATING

- From -67°F to 176°F

APPROVALS

- UL Listed to standard UL924 & CAN/ULC-S572
- NFPA 101 Life Safety Code
- NEC Article 500, Class 1, 11, and 111 conditions

WARRANTY

- Our self-luminous products are warranted against any defects in material or workmanship for the rated life of the product. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website

DIMENSIONS
