

CEL

Chicago Emergency Light

DATE:

PROJECT

COMMENTS:



FEATURES

- City of Chicago approved
- Two, 6V adjustable white LED lamp heads in metal housing and PC lens provide optimal light distribution
- 3.3W (3 LEDs x 1.1W) per head with a light output of 335 lumens
- Unique bi-color LED indicator light alerts occupant on battery condition (Green/normal, Red-check battery)
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- LVD (low voltage disconnect) prevents battery from deep discharge
- Internal solid-state transfer switch automatically connects the internal battery to the LED lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours



ORDERING INFORMATION *CEL-BK-MB*

1. SERIES

CEL

2. HOUSING

-

BK Black
WH White

3. MOUNTING

-

MB

MB Back Mount

ACCESSORIES; ORDER SEPARATELY

- WG 1 = Wire guard 17.0" X 17.0" X 17.0"

ELECTRICAL

- Dual 120/277 voltage
- 6V sealed lead acid, maintenance-free, rechargeable battery
- Remote capacity of 5.4W standard

CONSTRUCTION

- Durable, 20-gauge steel housing
- White or black powder coat finish

TEMPERATURE RATING

- From 68°F to 122°F

MOUNTING

- Knockouts on the back for wall mount
- Side and top knockouts for conduit feed applications

APPROVALS

- City of Chicago Approved
- UL 924
- UL Listed for Damp Location
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA

WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.

DIMENSIONS

