

DATE: _____	COMMENTS: _____
PROJECT _____	_____



FEATURES

- Approved in the City of Chicago.
- Attractive, contemporary steel housing design that is UL listed for use in damp locations.
- White LEDs offer great energy efficiency with high output.
- Charge rate/power ON LED indicator light, and push to test switch for mandated code compliance testing.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 2 hour emergency illumination.
- Available in single or double face configurations.
- Maintenance free nickel cadmium batteries are rechargeable and offer a long product life.
- 120/277 VAC with field selectable inputs.



ORDERING INFORMATION *CLP-AC-R-CHI2-BK-MTEB*

1. SERIES	2. OPERATIONS	3. ILLUMINATION	4. FACE COUNT
CLP	-	R	-
	AC AC Only EM Ni-Cad Battery Backup	R Red	CHI2 Single Face Stairs No Arrow CHI3 Single Face Exit No Arrow CHI5 Single Face Stairs Right Arrow CHI6 Single Face Exit Right Arrow CHI8 Single Face Stairs Left Arrow CHI9 Single Face Exit Left Arrow CHI12 Single Face Exit Double Arrow CHI17 Double Face Stairs No Arrow CHI18 Double Face Exit No Arrow CHI20 Double Face Stairs Right or Left Arrow CHI21 Double Face Exit Right or Left Arrow CHI23 Double Face Stairs Double Arrow CHI24 Double Face Exit Double Arrow
5. FRAME COLOR	6. MOUNTING		
BK Black WH White	MTEB		
	MTEB Top/End/Back Mount		

ACCESSORIES; ORDER SEPARATELY

- **WG-16.5LX14.0WX3.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 3"
- **WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- **WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- **WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

NOTE: Wireguards only available with Back Mount.

SPECIFICATIONS
CONSTRUCTION

- Durable 20-gauge steel
- Neutral powder coated white finish

MOUNTING

- Side and back knockouts are provided for mounting convenience.
- Canopy is provided for universal (top, end, or back) mounting.

LETTERS

- 6" high; 0.75" stroke

ARROWS

- Chicago Approved Arrows

WEIGHT

- **AC:** 7.5 lb
- **EM:** 8 lb

TEMPERATURE RATING

- From 32°F to 122°F

APPROVALS

- City of Chicago Approved
- CEC Title 20 Compliant
- UL 924
- UL Listed for Damp Location
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA
- NAFTA

WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS
