



CLPC

Chicago Approved LED Exit & Emergency Combo

DATE:

PROJECT

COMMENTS:



FEATURES

- Approved in the City of Chicago.
- Features two 5.3W adjustable LED lamp heads.
- Attractive, contemporary steel housing design that is UL listed for use in damp locations.
- White LEDs offer great energy efficiency with high output.
- Charge rate/power ON LED indicator light, and push to test switch for mandated code compliance testing.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 2 hour emergency illumination.
- Available in single or double face configurations.
- Maintenance free nickel cadmium batteries are rechargeable and offer a long product life.
- 120/277 VAC with field selectable inputs.

ORDERING INFORMATION *CLPC-R-CHI2-BK-MTEB*

1. SERIES	2. ILLUMINATION	3. FACE COUNT	4. FRAME COLOR
CLPC	R		
	R Red	CHI2 Single Face Stairs No Arrow	BK Black
		CHI3 Single Face Exit No Arrow	WH White
		CHI5 Single Face Stairs Right Arrow	
		CHI6 Single Face Exit Right Arrow	
		CHI8 Single Face Stairs Left Arrow	
		CHI9 Single Face Exit Left Arrow	
		CHI11 Single Face Stairs Double Arrow	
		CHI12 Single Face Exit Double Arrow	
		CHI17 Double Face Stairs No Arrow	
		CHI18 Double Face Exit No Arrow	
		CHI20 Double Face Stairs Right or Left Arrow	
		CHI21 Double Face Exit Right or Left Arrow	
		CHI23 Double Face Stairs Double Arrow	
		CHI24 Double Face Exit Double Arrow	
5. MOUNTING	6. OPTIONS		
MTEB			
MTEB Top/End/Back Mount	EB Remote Capacity ¹		

ORDERING NOTES

1. Remote Capacity (EB) option allows 10W of remote capacity at 6V.

ACCESSORIES; ORDER SEPARATELY

- **WG-16.75LX13.3WX6.0D** = Wireguard, Length: 16.75", Width: 13.3", Depth: 6"

NOTE: Wireguards only available with Back Mount.

SPECIFICATIONS

CONSTRUCTION

- Durable 20-gauge steel
- Neutral powder-coated white finish

MOUNTING

- Side and back knockouts are provided for mounting convenience.
- Canopy is provided for universal (top, end, or back) mounting.

LETTERS

- 6" high; 0.75" stroke

ARROWS

- Chicago Approved Arrows

TEMPERATURE RATING

- From 68°F to 122°F (20°C to 50°C)

APPROVALS

- City of Chicago Approved
- CEC Title 20 Compliant
- UL 924
- UL Listed for Damp Location
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA
- NAFTA

WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

