



CLS

Chicago Approved LED Emergency Light

DATE:

COMMENTS:

PROJECT

Product Discontinued.



FEATURES

- Approved for use in the city of Chicago.
- 27-100 watt capacity available.
- Uses a maintenance-free sealed lead calcium battery to provide a UL listed 90 minute runtime.
- Two metal lamp heads use 12 watt PAR36 style lamps.
- UL listed for use in damp locations.
- Side and top conduit knockouts allow for easy installation.
- 120/277 VAC with field selectable inputs.

ORDERING INFORMATION *CLS-6V27W-BK-MB*

1. SERIES

CLS

2. OPERATIONS

- 6V27W 6 Volts, 27 Watts
- 6V50W 6 Volts, 50 Watts
- 6V100W 6 Volts, 100 Watts
- 12V50W 12 Volts, 50 Watts
- 12V100W 12 Volt, 100 Watt

3. FRAME COLOR

- BK Black
- WH White

4. MOUNTING

MB

MB Back Mount

ACCESSORIES; ORDER SEPARATELY

- **WG-16.5LX14.0WX3.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 3"
- **WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- **WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- **WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

SPECIFICATIONS

CONSTRUCTION

- Durable, 20-gauge steel housing
- White or black powder coat finish

TEMPERATURE RATING

- From 68°F to 122°F

WEIGHT

- **27 Watt:** 10.5 lbs
- **50 Watt:** 16 lbs
- **100 Watt:** 25 lbs

APPROVALS

- City of Chicago Approved
- UL 924
- UL Listed for Damp Location
- NFPA Life Safety Code 101
- NFPA 70- NEC
- OSHA
- NAFTA
- BAA Compliant

WARRANTY

- Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.



DIMENSIONS

