

CLS

Chicago Approved LED Emergency Light

DATE:	COMMENTS:
PROJECT	



FEATURES

- Approved for use in the city of Chicago.
- 27-100 watt capacity available.
- Uses a maintenance-free sealed lead calcium battery to provide a UL listed 90 minute runtime.
- Two metal lamp heads use 12 watt PAR36 style lamps.
- UL listed for use in damp locations.
- Side and top conduit knockouts allow for easy installation.
- 120/277 VAC with field selectable inputs.





ORDERING INFORMATION CLS-6V27W-BK-MB

1. SERIES	2. OPERATIONS	3. FRAME COLOR	4. MOUNTING
CLS	-	-	- MB
	6V27W 6 Volts, 27 Wat 6V50W 6 Volts, 50 Wat 6V100W 6 Volts, 100 Wa	tts WH White	MB Back Mount

ACCESSORIES; ORDER SEPARATELY

WG-16.5LX14.0WX3.0D = Wireguard, Length: 16.5", Width: 14", Depth: 3"

12V50W 12 Volts, 50 Watts **12V100W** 12 Volt, 100 Watt

- WG-16.5LX14.0WX6.0D = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- WG-20.0LX19.0WX9.0D = Wireguard, Length: 20", Width: 19", Depth: 9"
- WG-26.0LX19.0WX9.0D = Wireguard, Length: 26", Width: 19", Depth: 9"

SPECIFICATIONS

CONSTRUCTION

- Durable, 20-gauge steel housing
- White or black powder coat finish

TEMPERATURE RATING

From 68°F to 122°F

WEIGHT

27 Watt: 10.5 lbs50 Watt: 16 lbs100 Watt: 25 lbs

APPROVALS

- City of Chicago Approved
- UL 924
- UL Listed for Damp Location
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA
- NAFTA
- BAA Compliant

WARRANTY

Isolite offers a 3-year limited warranty.
For further details, refer to General
Warranty and Obligations in the Isolite manual or on our website.







DIMENSIONS

