

DCL

Die-Cast LED Exit & Emergency Combo

DATE:	COMMENTS:
PROJECT:	

FEATURES

- Ultra-bright, energy efficient, long-life Red or Green LED
- High performance, premium grade, ultra-bright white LED emergency lamps
- 3 watts per head
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- 8.4V long-life, maintenance-free, rechargeable Ni-Cad battery
- Optional 3 watts remote capacity (EB)
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours
- 120/277 VAC field-selectable inputs



CEC Title 20



ORDERING INFORMATION *DCL-R-2-BA-BA-MTEBP*

1. SERIES	2. LETTERS	3. FACES	4. FACE COLOR	5. FRAME COLOR
DCL	-	-	-	-
	R Red G Green	1 Single 2 Double U Universal	BA Brushed Aluminum Face BK Black Face WH White Face	BA Brushed Aluminum Face BK Black Face WH White Face
6. MOUNTING	7. OPTIONS	ACCESSORIES; ORDER SEPERATELY		
MTEBP	-	<ul style="list-style-type: none"> ▪ WG5 = Wire Guard Wall Mount 15.75 x 14.75 x 6.75 ▪ WG10 = Wire Guard Ceiling Mount 13.5 x 12 x 16.5 		
MTEBP Universal Mount	BLANK = NO OPTION EB Remote Capacity			

SPECIFICATIONS

CONSTRUCTION

- Premium-grade, extruded aluminum housing. Available in black or white powder-coat finishes

ARROWS

- Field selectable knockout chevron directional indicators

APPROVALS

- UL 924
- UL Listed for Damp Location
- CEC Title 20 Compliant
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA

WEIGHT

- 7 lb

TEMPERATURE RATING

- From 32°F to 122°F

WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted

DIMENSIONS

