



DCL

Die-Cast LED Exit & Emergency Combo

DATE:

PROJECT

COMMENTS:



FEATURES

- Lettering with ultra-bright, energy efficient, long life red or green LED.
- 3W emergency lamp heads with high performance, premium grade, ultra-bright white LED.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 8.4V rechargeable, maintenance Ni-Cad battery with long-life.
- EB options allows for 3W remote capacity.
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- 120/277 VAC with field selectable inputs.

CEC Title 20



ORDERING INFORMATION *DCL-R-2-BA-BA-MTEBP*

1. SERIES	2. LETTERS	3. FACES	4. FACE COLOR	5. FRAME COLOR
DCL	-	-	-	-
	R Red G Green	1 Single 2 Double U Universal	BA Brushed Aluminum Face BK Black Face WH White Face	BA Brushed Aluminum Face BK Black Face WH White Face
6. MOUNTING	7. OPTIONS			
MTEBP	-			
MTEBP Universal Mount	BLANK = NO OPTION EB Remote Capacity			

ACCESSORIES; ORDER SEPARATELY

- **WG-16.5LX14.0WX3.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 3"
- **WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- **WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- **WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

NOTE: Wireguards only available with Back Mount.

SPECIFICATIONS

CONSTRUCTION

- Premium-grade, extruded aluminum housing. Available in black or white powder-coat finishes.

ARROWS

- Field selectable knockout chevron directional indicators

WEIGHT

- 7 lbs

TEMPERATURE RATING

- From 32°F to 122°F


APPROVALS

- UL 924
- UL Listed for Damp Location
- CEC Title 20 Compliant
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA

WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.

DIMENSIONS



LAMP SPACING

MOUNTING HEIGHT	CENTER-TO-CENTER SPACING
6.0'	22'
6.5'	21'
7.0'	19'
7.5'	18'
8.0'	17'