

DATE:

COMMENTS:

PROJECT



FEATURES

- Combines two Eco-friendly technologies: LED and Photoluminescence
- Maintenance-free LED light source illuminates the letters in normal AC power
- Non-electrical Photoluminescence illuminates the letters when AC power fails
- Requires only 2 Watts of electrical power
- Eliminates the need for any auxiliary power or external charging light sources
- No batteries required
- Polycarbonate security cover and wire guards available
- Vandal resistant and tamper proof polycarbonate shield available
- Recessed power supply for all units
- Zero current, low-voltage disconnect
- Unique electronic driver circuit provides current control and protection, ensuring optimum LED efficiency and life
- 120/277 VAC field-selectable inputs



ORDERING INFORMATION *DTH-G-1-BA-BA-MB*

1. SERIES

DTH

2. ILLUMINATION

G

G Green

3. FACE COUNT

1 Single
2 Double

4. FACE COLOR

BA Brushed Aluminum
BK Black
WH White

5. FRAME COLOR

BA Brushed Aluminum
BK Black
WH White

6. MOUNTING

MB Back Mount
MRW Recessed Wall Mount
MPA 12" Swivel Pendant Kit
MPB 24" Swivel Pendant Kit
MPC 36" Swivel Pendant Kit
MPD 48" Swivel Pendant Kit
MTEB Top/End/Back Mount

7. OPTIONS

BLANK = NO OPTION
LD Damp Location
TP Tamper proof Screws
VRA Vandal Resistant Lens (1/8 in) (Incl. TP)
VRB Vandal Resistant Lens (1/4 in) (Incl. TP)

ACCESSORIES; ORDER SEPARATELY

- WG 2 = Wireguard 14" X 10" X 4.5"
- WG 3 = Wireguard 14.5" X 6" X 10.5"
- WG 10 = Wireguard 13.5" X 12" X 16.5"

CONSTRUCTION

- Injection molded internal cavity reflector provides ease of installation and maintenance together with perfectly even legend illumination
- Two piece, heavy-duty walls constructed from die cast aluminum alloy
- Removable front stencil face with overlapping light seal
- Hidden knock out access points and universal pattern
- Optional recess frame, polycarbonate face shield with tamper proof access screws, and pendant & specialty mounts

LETTERS

- 6" high; 0.75" stroke

ARROWS

- NFPA type, universal field-selectable chevrons

WEIGHT

- 4.5 lbs

CANOPY SIZE

- 4.75" x 4.75" x 0.75"

APPROVALS

- UL 924
- CEC Title 20 Compliant
- NFPA 101 Life Safety Code
- NFPA 70- NEC
- OSHA

WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website

DIMENSIONS
