



DTH - Dual Tech Hybrid Exit

Photoluminescent/LED Die-Cast Exit Sign

DATE:

COMMENTS:

PROJECT



FEATURES

- Internal LEDs are used to charge the photoluminescent material internally for an eco-friendly solution.
- Maintenance-free LED light source illuminates the letters in normal AC power.
- Non-electrical photoluminescence illuminates the letters when AC power fails.
- Requires only 2 watts of power to operate.
- Eliminates the need for any auxiliary power, batteries, or external charging light sources.
- Polycarbonate security cover and wire guards are available.
- Vandal resistant and tamper proof polycarbonate shield are available.
- Recessed power supply is provided for all units.
- Zero current, low-voltage disconnect used to prevent battery from being overly discharged.
- Unique electronic driver circuit provides current control and protection, ensuring optimum LED efficiency and long life expectancy.
- 120/277 VAC with field selectable inputs.
- UL listed for use in damp locations.



ORDERING INFORMATION *DTH-G-1-BA-BA-MB*

1. SERIES

DTH

2. ILLUMINATION

G

G Green

3. FACE COUNT

- 1 Single
- 2 Double

5. FACE & FRAME COLOR

- BA-BA All Brushed Aluminum
- BA-BK Brushed Aluminum Face / Black Body
- BA-WH Brushed Aluminum Face / White Body
- BK-BK All Black
- WH-WH All White
- CC Custom Color

6. MOUNTING

- MB Back Mount
- MRW Recessed Wall Mount
- MPA 12" Swivel Pendant Kit
- MPB 24" Swivel Pendant Kit
- MPC 36" Swivel Pendant Kit
- MPD 48" Swivel Pendant Kit
- MTEB Top/End/Back Mount

7. OPTIONS

- BLANK = NO OPTION
- TP Tamper proof Screws
- VRA Vandal Resistant Lens (1/8 in) (Incl. TP)
- VRB Vandal Resistant Lens (1/4 in) (Incl. TP)

ACCESSORIES; ORDER SEPARATELY

- WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

NOTE: Wireguards only available with Back Mount.



SPECIFICATIONS

CONSTRUCTION

- Injection molded internal cavity reflector provides easy installation and maintenance with perfectly even legend illumination.
- Two piece, heavy-duty walls are constructed from die cast aluminum alloy.
- Front stencil face has an overlapping light seal for no light leakage.
- Hidden knock out access points with a universal pattern.
- Recessed frame, polycarbonate face shields with tamper proof screws, and specialty mounts/pendants are available upon request.

LETTERS

- 6" high; 0.75" stroke

ARROWS

- NFPA type, universal field selectable chevrons.

WEIGHT

- 4.5 lbs

CANOPY SIZE

- 4.75" x 4.75" x 0.75"

TEMPERATURE RATING

- 50°F to 122°F (10°C to 40°C)

APPROVALS

- UL 924
- CEC Title 20 Compliant
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA
- BAA Compliant

WARRANTY

- Isolite offers a lifetime warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

