

DATE:

PROJECT

COMMENTS:

FEATURES

- Thin architectural profile
- Combines two Eco-friendly technologies: LED and Photoluminescence
- Maintenance-free LED light source illuminates the letters in normal AC power
- Non-electrical Photoluminescence illuminates the letters when AC power fails
- Requires only 2 Watts of electrical power
- Eliminates the need for any auxiliary power or external charging light sources
- No batteries required
- Thin architectural profile
- Optional Vandal resistant and tamper proof polycarbonate shield available, makes the sign suitable for Floor Proximity applications
- Zero current low-voltage disconnect
- Unique electronic driver circuit provides current control and protection, ensuring optimum LED efficiency and life
- 120/277 VAC field-selectable inputs
- 100' Viewing Distance in photoluminescence and LED modes of operation



ORDERING INFORMATION *DTH2-1-BA-MB*

1. SERIES	2. FACE COUNT	3. FRAME COLOR	4. MOUNTING	5. OPTIONS
DTH2	-	-	-	-
	1 Single 2 Double U Universal	BA Brushed Aluminum BK Black WH White BR Painted Brass	MB Back Mount MPA 12" Swivel Pendant Kit MPB 24" Swivel Pendant Kit MPC 36" Swivel Pendant Kit MPD 48" Swivel Pendant Kit MTEB Top/End/Back Mount	BLANK = NO OPTION VR 1/8" Vandal Resistant Lens

ACCESSORIES; ORDER SEPARATELY

- WG 2 = Wireguard 14" X 10" X 4.5"
- WG 3 = Wireguard 14.5" X 6" X 10.5"
- WG 10 = Wireguard 13.5" X 12" X 16.5"

CONSTRUCTION

- Injection molded internal cavity reflector provides ease of installation and maintenance together with perfectly even legend illumination
- Two piece, heavy-duty walls constructed from die cast aluminum alloy
- Removable front stencil face with overlapping light seal
- Hidden knock out access points and universal pattern

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- NFPA type, universal field-selectable chevrons

WEIGHT

- 8 lbs

APPROVALS

- UL 924
- UL 924 Damp Location Approved
- UL 924 Floor Proximity (with VR option)
- CEC Title 20 Compliant
- NFPA 101 Life Safety Code
- NFPA 70- NEC
- OSHA
- NAFTA

WARRANTY

- Isolite offers a **lifetime** warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website

DIMENSIONS

