

DATE:	COMMENTS:
PROJECT:	

FEATURES

- Includes a 6" International Symbol of Accessibility or Dynamic Symbol of Accessibility
- Long life Nickel Cadmium maintenance free battery provides the required 90 minutes of emergency operation
- Electronic Control Circuit and Isolation Transformer provide current control and circuit protection, ensuring optimum LED efficiency and life
- Solid state transfer relay ensures reliability-no relay contacts to oxidize and fail
- External LED monitor light and test switch are standard on self-powered versions
- High-output, energy efficient LED technology
- Line-Latch prevents unnecessary discharge of battery
- Brownout detection ensures emergency operation during periods of low line voltage
- LED AC present indicator and push-to-test switch
- 120/277 VAC field-selectable inputs



SYMBOL KEY



DSA = Dynamic Symbol of Accessibility (CT)

ISA = International Symbol of Accessibility (MA)

ORDERING INFORMATION *ECTMA-AC-G-1C-DSA-BA-MB*

1. SERIES	2. OPERATION	3. COLOR	4. FACE COUNT	5. SYMBOL
ECTMA	-	-	-	-
	AC AC Only EM Ni-Cad Battery Backup	G Green R Red	1C Single Face, Clear Background 1M Single Face, Mirror Background 1W Single Face, White Background 2M Double Face, Mirror Background 2W Double Face, White Background	DSA Dynamic Symbol of Accessibility (CT) ISA International Symbol of Accessibility (MA)
6. FRAME COLOR	7. MOUNTING	8. OPTIONS		
BA Brushed Aluminum Frame WH White Frame	MB Back Mount (Surface Wall) ME End Mount / Side Mount MP Pendant Mount MRC Recessed Ceiling Mount MRW Recessed Wall Mount MT Top Mount	BLANK = NO OPTION EB Extended Run Time		

ACCESSORIES; ORDER SEPARATELY

- WG 6 = Wire guard 20.0" X 17.0" X 12.0"

CONSTRUCTION

- Durable 20 gauge steel
- White-baked powder coat finish
- High clarity acrylic

LETTERS

- 6" high; 0.75" stroke

ARROWS

- NFPA-Type, universal field selectable chevrons

WEIGHT

- 6 lb

TEMPERATURE RATING

- From 50°F to 113°F

APPROVALS

- CSA-US listed
- Meets or exceeds UL 924 standards
- State of Connecticut Building Code Paragraph 1011.1.2
- NFPA 101 Life Safety Code
- NFPA 70- NEC
- OSHA

WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted

DIMENSIONS
