

DATE:	COMMENTS:
PROJECT:	

FEATURES

- Ultra-bright, energy efficient, long-life Red or Green LEDs
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours
- 4.8V long-life, maintenance-free, rechargeable Ni-Cad battery
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- 120/277 VAC field-selectable inputs (with the exception of the CX (dual circuit) option)



ORDERING INFORMATION *EDC-EM-G-U-BA-BA-MTEBP*

1. SERIES	2. OPERATION	3. COLOR	4. FACES	5. FACE COLOR	6. FRAME COLOR	7. MOUNTING
EDC	-	-	-	-	-	MTEBP
	AC AC Only EM Ni-Cad Battery Backup	G Green R Red	1 Single 2 Double U Universal	BA Brushed Aluminum BK Black WH White	BA Brushed Aluminum BK Black WH White	MTEBP Universal Mount

8. OPTIONS

BLANK = NO OPTION

- SD Self-Diagnostics¹
- CX Dual Circuit - 120/277 VAC²
- TP Tamperproof Screws

ORDERING NOTES

- EM Operation only
- AC Operation only

ACCESSORIES; ORDER SEPERATELY

- WG 2 = Wireguard Wall Mount 14" X 10" X 4.5"
- WG 3 = Wireguard Ceiling Mount 14.5" X 6" X 10.5"
- WG 10 = Wireguard End Mount 13.5" X 12" X 16.5"

SPECIFICATIONS

ARROWS

- Field selectable knockout chevron directional indicators

CONSTRUCTION

- Premium-grade, aluminum housing. Also available in black or white powder-coat finishes

WEIGHT

- 5 lb

APPROVALS

- UL 924
- UL Listed for Damp Location
- CEC Title 20 Compliant
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA

TEMPERATURE RATING

- From 32°F to 122°F

WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted

DIMENSIONS

