

DATE:

PROJECT

COMMENTS:

## FEATURES

- New York City Approved 8" letters with 1" stroke
- Ultra-bright, energy efficient, long-life Red or Green LEDs
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours
- 4.8V long-life, maintenance-free, rechargeable Ni-Cad battery
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- 120/277 VAC field-selectable inputs (with the exception of the C1/C2 (dual circuit) option which requires voltage specification upon ordering)



## ORDERING INFORMATION *EXAMPLE: EDC-NYC-AC-R-1-BA-BA-MTEBP*

### 1. SERIES

**EDC-NYC**

### 2. OPERATION

**AC** AC Only  
**EM** Ni-Cad Battery Backup

### 3. ILLUMINATION

**R**

**R** Red

### 4. FACE COUNT

**1** Single  
**2** Double  
**U** Universal

### 5. FACE COLOR

**BA** Brushed Aluminum  
**BK** Black  
**WH** White

### 6. FRAME COLOR

**BA** Brushed Aluminum  
**BK** Black  
**WH** White

### 7. MOUNTING

**MTEBP**

**MTEBP** Universal Mount

### 8. OPTIONS

**BLANK = NO OPTION**  
**CX** Dual Circuit (120/277 VAC) (AC Only)  
**SD** Self-Diagnostics (EM Only)  
**TP** Tamperproof Screws



**ARROWS**

- Field selectable knockout chevron directional indicators

**CONSTRUCTION**

- Premium-grade, aluminum housing. Also available in black or white powder-coat finishes

**WEIGHT**

- • 5 lb

**TEMPERATURE RATING**

- From 32°F to 122°F

**APPROVALS**

- New York City Approved
- UL 924
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA

**WARRANTY**

- Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted

**DIMENSIONS**

