



ELP

High Output LED Thermoplastic Emergency Light

DATE:

PROJECT

COMMENTS:

FEATURES

- Includes two adjustable 6W LED lighting heads that can be field modified for side-mount applications.
- Includes 38W remote capacity for 50W, and 88W remote capacity for 100W.
- Provides up to 100-ft spacing at 15-ft mounting height.
- Keyhole mounting slots and conduit knockouts are provided for additional mounting possibilities.
- UL listed for a minimum run-time of 90 minutes.
- Utilizes a maintenance free, sealed lead acid battery.
- Snap fit door is secured by nickel plated steel counter sunk screws.
- Momentary test switch and AC status indicator are used to monitor normal and emergency power operation.
- Line-latch prevents unnecessary discharge of battery during installation. Loads will not illuminate until after application of utility power.
- Low voltage cut-off prevents battery damage and ensures positive charge acceptance following an extended discharge.
- Brownout sensing ensures emergency operation during periods of low line voltage.
- 120/277 VAC with field selectable inputs.



ORDERING INFORMATION *ELP-6V50W-BK-MB-2-L66*

1. SERIES	2. OPERATION	3. HOUSING COLOR	4. MOUNTING	5. HEAD COUNT	6. LAMPS
ELP	-	-	MB	2	-
	6V50W 6 Volts, 50 Watts 6V100W 6 Volts, 100 Watts 12V50W 12 Volts, 50 Watts 12V100W 12 Volt, 100 Watt	BK Black WH White	MB Back Mount	2 Two Heads	L66 6 Volts, 6 Watts L126 12 Volts, 6 Watts

SPECIFICATIONS

CONSTRUCTION

- Injection Molded ABS housing with a 5VA flame retardant thermoplastic rating.

TEMPERATURE RATING

- From 68°F to 104°F

APPROVALS

- UL 924
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA

WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.

DIMENSIONS

