

DATE:	COMMENTS:
PROJECT:	

FEATURES



- Designed for installation into a ceiling or wall.
- Two fully adjustable, top mounted, MR16 style lighting heads in high impact thermoplastic are standard. Additional lamp types and wattages available for lighting heads.
- Capable of powering multiple remote heads.
- External test switch and monitor LED are standard.
- Unique locking twist-collar securely holds the lens for quick and easy re-lamping.
- Low voltage cut-off prevents battery damage and ensures positive charge acceptance following an extended discharge.
- Self-Test/Self-Diagnostic monitoring is available.
- Uses maintenance free sealed lead calcium or nickel cadmium battery for 90 minute emergency run time.
- Short circuit battery protection is standard in all units.
- Brownout detection ensures emergency operation during periods of low line voltage.
- Line-latch prevents unnecessary discharge of battery during installation. Loads will not illuminate until after application of utility power.
- Removable side access panel are provided for easy service and installation.
- 120/277 VAC with field selectable inputs.



ORDERING INFORMATION *ERG-LC-6V18W-BK-MCG-2-XRH-B610*

1. SERIES	2. BATTERY TYPE	3. OPERATION	4. FRAME COLOR	5. MOUNTING
ERG	-	-	-	MCG
	LC Lead Calcium Battery Backup	6V18W 6 Volts, 18 Watts 12V27W 12 Volts, 27 Watts 6V27W 6 Volts, 27 Watts 12V36W 12 Volts, 36 Watts	BK Black Frame WH White Frame	MCG Ceiling Grid Mount
	NC Ni-Cad Battery Backup	6V22W 6 Volts, 22 Watts 6V42W 6 Volts, 42 Watts 12V42W 12 Volts, 42 Watts		
6. HEAD COUNT	6. HEAD STYLE	7. LAMPS ¹	8. OPTIONS	
0 No Heads 1 One Head 2 Two Heads	XRH XRH Lamp Heads	L65 LED 6V 5W L67 LED 6V 7W L122 LED 12V 2W L125 LED 12V 5W L127 LED 12V 7W	BLANK = NO OPTION SD Self-Diagnostics AA Audible Alarm (Buzzer) TD Time Delay - 120/277 VAC (15 min)	

ORDERING NOTES

1. Additional lamp options may be available, please contact Quotes@Isolite.com if non-LED lamps are required.

DIMENSIONS

CONSTRUCTION

- 20 gauge steel cabinet
- Durable, white powder-coat finish

TEMPERATURE RATING

- From 50°F to 104°F

APPROVALS

- CSA-US listed
- Meets or exceeds UL 924 standards
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA
- BAA Compliant

WARRANTY

- Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.

DIMENSIONS

