

DATE:

PROJECT:

COMMENTS:

FEATURES

- Super-bright, long-life LEDs
- Suitable for damp locations
- Unique pivoting housing suitable for ceiling, wall, or end mount applications
- Energy consumption less than 2 Watts of nominal power
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- Long life Nickel Cadmium, maintenance free battery
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours
- Brownout detection ensures emergency operation during periods of low line voltage
- 120/277 VAC field-selectable inputs



CEC Title 20



ORDERING INFORMATION *EUG-AC-G-1C-MPA*

1. SERIES	2. OPERATION TYPE	3. ILLUMINATION	4. FACE COUNT	5. MOUNTING
EUG	-	-	-	-
	AC AC Only EM Ni-Cad Battery Backup	G Green R Red	1C Single Face, Clear Background 2M Double Face, Mirror Background	MTEB Top/End/Back Mount MPA 12" Swivel Pendant Kit MPB 24" Swivel Pendant Kit MPC 36" Swivel Pendant Kit MPD 48" Swivel Pendant Kit

ACCESSORIES; ORDER SEPERATELY

- EUNR1M = Conversion Panel, Single Face, Red Letters, Mirror Background
- EUNG1M = Conversion Panel, Single Face, Green Letters, Mirror Background
- WG 2 = Wire guard 14.0" X 10.0" X 4.5"

SPECIFICATIONS

CONSTRUCTION

- Attractive, low profile satin extruded aluminum with matching gray end-caps
- Clear acrylic, edge-lit lens is provided for single faced signs, mirrored background is standard for double faced signs

ARROWS

- NFPA-Type, universal field installable, self-adhesive chevrons

DIMENSIONS

LETTERS

- 6" high; 0.75" stroke

APPROVALS

- UL924
- CEC Title 20 Compliant
- NFPA 101 Life Safety Code
- NEC NFPA 70
- OSHA

TEMPERATURE RATING

- From 50°F to 104°F

WEIGHT

- 3.2 lb

WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website

