

DATE:

PROJECT

COMMENTS:



## FEATURES

- Super-bright LEDs with long life expectancy.
- Suitable for damp locations.
- Unique pivoting housing suitable for ceiling, wall, or end mount applications.
- The energy consumption is less than 2 watts of nominal power.
- Charge rate/power "ON" LED indicator light and push-to-test switch are provided for mandated code compliance testing.
- Maintenance free nickel cadmium batteries with long life expectancy.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Full automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours while reducing overcharge and improving the life of the battery.
- Brownout detection ensures emergency operation during periods of low line voltage.
- 120/277 VAC with field selectable inputs.



## ORDERING INFORMATION *EUG-AC-G-1C-MTEB*

| 1. SERIES  | 2. OPERATION TYPE                      | 3. ILLUMINATION  | 4. FACE COUNT   | 5. MOUNTING             |
|------------|--|------------------|---|-------------------------|
| <b>EUG</b> | -                                      | -                | -   | <b>MTEB</b>             |
|            | AC AC Only<br>EM Ni-Cad Battery Backup | G Green<br>R Red | 1C Single Face, Clear Background<br>2M Double Face, Mirror Background | MTEB Top/End/Back Mount |

## ACCESSORIES; ORDER SEPARATELY

- **EUNR1M** = Conversion Panel, Single Face, Red Letters, Mirror Background
- **EUNG1M** = Conversion Panel, Single Face, Green Letters, Mirror Background
- **EUNR2M** = Conversion Panel, Double Face, Red Letters, Mirror Background
- **EUNG2M** = Conversion Panel, Double Face, Green Letters, Mirror Background
- **PKIT1-WH-12** = 12" Swivel Mounting Pendant Kit, White
- **PKIT1-WH-24** = 24" Swivel Mounting Pendant Kit, White
- **PKIT1-WH-36** = 36" Swivel Mounting Pendant Kit, White
- **PKIT1-WH-48** = 48" Swivel Mounting Pendant Kit, White
- **PKIT1-BK-12** = 12" Swivel Mounting Pendant Kit, Black
- **PKIT1-BK-24** = 24" Swivel Mounting Pendant Kit, Black
- **PKIT1-BK-36** = 36" Swivel Mounting Pendant Kit, Black
- **PKIT1-BK-48** = 48" Swivel Mounting Pendant Kit, Black
- **WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- **WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- **WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

NOTE: Wireguards only available with Back Mount.

**SPECIFICATIONS**
**CONSTRUCTION**

- Attractive, low profile satin extruded aluminum with matching gray end-caps.
- Clear acrylic, edge-lit lens is provided for single faced signs while mirrored background is standard for double faced signs.

**ARROWS**

- NFPA-type, universal field installable, self-adhesive chevrons.

**LETTERS**

- 6" high; 0.75" stroke

**TEMPERATURE RATING**

- From 50°F to 104°F

**APPROVALS**

- UL 924
- CEC Title 20 Compliant
- NFPA 101 Life Safety Code
- NEC NFPA 70
- OSHA

**WARRANTY**

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

**DIMENSIONS**
