

LP-CTMA

Steel Connecticut & Massachusetts Compliant LED Mobility Exit Sign

DATE:	COMMENTS:
PROJECT:	

FEATURES

- Complies with the State of Connecticut Building Code requirements, and provides an EXIT sign with a 6.0" International Symbol of Accessibility
- Universal Mounting pattern stamped into the back plate for easy surface Mounting to a J-box
- Long life nickel cadmium maintenance-free battery provides the required 90 minutes of emergency operation
- Electronic Control Circuit and Isolation Transformer provide current control and circuit protection, ensuring optimum LED efficiency and life
- Solid-state transfer relay ensures reliability — no relay contacts to oxidize and fail
- High-output, energy efficient LED technology
- Line latch prevents unnecessary discharge of battery
- Brownout detection ensures emergency operation during periods of low line voltage
- LED AC present indicator and push-to-test switch
- 120/277 VAC field selectable inputs



SYMBOL KEY



DSA = Dynamic Symbol of Accessibility (CT)



ISA = International Symbol of Accessibility (MA)

ORDERING INFORMATION *LP-CTMA-AC-G-1-DSA-WH-MB*

1. SERIES	2. BATTERY	3. ILLUMINATION	4. FACE COUNT	4. SYMBOL
LP-CTMA	-	-	-	-
	AC AC Only EM Ni-Cad Battery Backup	G Green R Red	1 Single 2 Double U Universal	DSA Dynamic Symbol of Accessibility (CT) ISA International Symbol of Accessibility (MA)
6. FRAME COLOR	7. MOUNTING	8. OPTIONS		
WH White BK Black	MB Back Mount MTEBP Universal Mount MPAB 12" Swivel Mount (Black) MPABA 12" Swivel Mount (Brushed Aluminum) MPAW 12" Swivel Mount (White)	BLANK = NO OPTION EB Extended Run-time (EM Only) AA Audible Alarm (Buzzer) FL Flasher FA Fire Alarm Interface		

ACCESSORIES; ORDER SEPARATELY

- WG 6 = Wire guard 20.0" X 17.0" X 12.0"



CONSTRUCTION

- Durable 20 gauge steel

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- NFPA-Type, universal field selectable chevrons

WEIGHT

- AC: 5.4 lbs.
- EM: 5.7 lbs.

TEMPERATURE RATING

- From 50°F to 113°F

APPROVALS

- CSA-US listed
- Meets or exceeds UL 924 standards
- State of Connecticut Building Code Paragraph 1011.1.2
- NFPA 101 Life Safety Code
- NFPA 70 - NEC
- OSHA
- NAFTA

WARRANTY

Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.

DIMENSIONS

