

DATE:	COMMENTS:
PROJECT:	

FEATURES

- Attractive, contemporary steel housing design
- Energy efficient high output LEDs
- As low as 1.1W power consumption
- Black or white baked, powder-coat finish standard
- Swivel Pendant Mounting available upon request
- Face-plates slide out for quick and easy installations
- Self-Test/Self-Diagnostic monitoring available
- Maintenance-free nickel cadmium battery
- Short-circuit battery protection
- Brownout detection ensures emergency operation during periods of low line voltage
- Line latch prevents unnecessary discharge of battery during installation — loads will not illuminate until after application of utility power
- Key hole Mounting slots and conduit knockouts are provided for additional Mounting options
- 120/277 VAC field selectable inputs (with the exception of the C1/C2 (Dual Circuit) option which requires voltage specification upon ordering)



ORDERING INFORMATION *LP-AC-G-1-WH-MB*

1. SERIES	2. OPERATION	3. ILLUMINATION	4. FACE COUNT	5. FRAME COLOR
LP	-	-	-	-
	AC AC Only EM Ni-Cad Battery Backup	G Green R Red	1 Single 2 Double U Universal	WH White BK Black

6. MOUNTING

MB Back Mount	MPBB 24" Pendant Mount (Black)	MPCW 36" Pendant Mount (White)
MTEBP Universal Mount	MPBBA 24" Pendant Mount (Brushed Aluminum)	MPDB 48" Pendant Mount (Black)
MPAB 12" Pendant Mount (Black)	MPBW 24" Pendant Mount (White)	MPDBA 48" Pendant Mount (Brushed Aluminum)
MPABA 12" Pendant Mount (Brushed Aluminum)	MPCB 36" Pendant Mount (Black)	MPDW 48" Pendant Mount (White)
MPAW 12" Pendant Mount (White)	MPCBA 36" Pendant Mount (Brushed Aluminum)	

7. OPTIONS

BLANK = NO OPTION	AA Audible Alarm (Buzzer)
C1 Dual Circuit (120 VAC) (AC Only)	FL Flasher
C2 Dual Circuit (277 VAC) (AC Only)	FA Fire Alarm Interface
SD Self-Diagnostics (EM Only)	TP Tamper-proof Screws
EB Extended Run-time (EM Only)	

ACCESSORIES; ORDER SEPARATELY

- WG 2 = Wireguard 14.0" X 10.0" X 4.5"
- WG 3 = Wireguard 14.5" X 6.0" X 10.5"
- WG 10 = Wireguard 13.5" X 12.0" X 16.5"

CONSTRUCTION

- Durable, 20 gauge steel

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- NFPA-Type, universal field selectable chevrons

WEIGHT

- AC: 4.75 lbs.
- EM: 5.25 lbs.

TEMPERATURE RATING

- From 50°F to 104°F

APPROVALS

- CSA-US listed
- CEC Title 20 Compliant
- Meets or exceeds UL 924 standards
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA

WARRANTY

Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

