



# LPDC2 - Hybrid

Photoluminescent/LED Die-Cast Aluminum LED Exit Sign

DATE: \_\_\_\_\_ COMMENTS: \_\_\_\_\_

PROJECT \_\_\_\_\_



## FEATURES

- 100-foot viewing distance.
- Internal LEDs charge internal photoluminescent material, which illuminates the letters when AC power fails.
- This device contains no batteries, expanding the expected lifetime to 25+ maintenance-free years.
- Requires no external light source.
- Installs and performs just like a normal battery-backed sign.
- Maintenance free with no lamps or batteries to replace.
- Specialized entry plug removes the need for knockouts, speeding up installation.
- Field-selectable 120/277 VAC inputs and quick-install whip connector.
- Optional polycarbonate face shield, tamper-proof screws, and damp/wet location capabilities.
- Lifetime warranty.



## ORDERING INFORMATION *LPDC2-HY-G-1-BA-BA-MB*

1. SERIES	2. ILLUMINATION	3. FACE COUNT	4. FACE COLOR	5. BODY COLOR
LPDC2-HY	G	-	-	-
	G Green	1 Single 2 Double U Universal	BA Brushed Aluminum WH White BK Black CC Custom	BA Brushed Aluminum WH White BK Black CC Custom
6. MOUNTING	7. OPTIONS			
MTEB Top/End/Back Mount MB Back Mount MS Stanchion Mount MDC Direct Conduit Entry MPA 12" Swivel Mount MPB 24" Swivel Mount MPC 36" Swivel Mount MPD 48" Swivel Mount MPE 60" Swivel Mount MPF 72" Swivel Mount	BLANK = NO OPTION LD Damp Location			

## ACCESSORIES; ORDER SEPARATELY

- **TLRT** = Infrared Remote Control
- **WG-16.5LX14.0WX3.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 3"
- **WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- **WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- **WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

NOTE: Wireguards only available with Back Mount.



## SPECIFICATIONS

### CONSTRUCTION

- Injection-molded reflector ensures easy installation, maintenance, and even illumination.
- Heavy-duty, three-piece die-cast aluminum housing with a removable front stencil and light seal.
- Sleek 2.5" profile with softened corners and chamfered edges.
- Optional polycarbonate face shield, tamper-proof screws, swivel pendant, and specialty mounts.

### LETTERS

- 6.0" high; 0.75" stroke

### ARROWS

- NFPA type, universal field selectable chevrons.

### VIEWING DISTANCE

- 100 foot visibility rating

### CANOPY

- Low-profile universal canopy with 0.75" cast nipple and locking nuts.

### APPROVALS

- UL 924 Listed to 100ft Visibility Distance
- CSA C22.2 No. 141-10
- CEC Title 20 Compliant
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA
- BAA Compliant

### WARRANTY

- Isolite offers a lifetime warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

## DIMENSIONS

