



LPDC2 - Hybrid

Photoluminescent/LED Die-Cast Aluminum LED Exit Sign

DATE:	COMMENTS:
PROJECT:	



FEATURES

- Internal LEDs are used to charge the photoluminescence material internally for an eco-friendly solution.
- Maintenance-free LED light source with a lifespan of 25+ years and less than 5W power consumption.
- Non-electrical photoluminescence illuminates the letters when AC power fails.
- Requires no electricity or external light source.
- Maintenance free with no lamps or batteries to replace.
- New entry plug eliminates knockouts, reducing installation time.
- 120/277 VAC with field selectable inputs with quick install whip connector.
- Fine grain brushed aluminum stencil trim standard with specialty finish upon request.
- Optional polycarbonate face shield, tamper-proof screws, swivel pendant, and specialty mounts.



ORDERING INFORMATION LPDC2-HY-AC-G-1-BA-BA-MB

1. SERIES	2. ILLUMINATION	3. FACE COUNT	4. BODY COLOR	5. FACE COLOR
LPDC2-HY	G	-	-	-
	G Green	1 Single 2 Double U Universal	BA Brushed Aluminum WH White BK Black CC Custom	BA Brushed Aluminum WH White BK Black CC Custom
6. MOUNTING	7. OPTIONS	-		
MTEB Top/End/Back Mount MB Back Mount ME End Mount MS Stanchion Mount MCE Direct Conduit Entry MPA 12" Swivel Mount MPB 24" Swivel Mount MPC 36" Swivel Mount MPD 48" Swivel Mount MPE 60" Swivel Mount MPF 72" Swivel Mount	BLANK = NO OPTION DL Damp Location LW Wet Location VR Vandal Shield TP Tamperproof Screws			

ACCESSORIES; ORDER SEPARATELY

- TLRT = Infrared Remote Control
- WG-16.5LX14.0WX3.0D = Wireguard, Length: 16.5", Width: 14", Depth: 3"
- WG-16.5LX14.0WX6.0D = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- WG-20.0LX19.0WX9.0D = Wireguard, Length: 20", Width: 19", Depth: 9"
- WG-26.0LX19.0WX9.0D = Wireguard, Length: 26", Width: 19", Depth: 9"

NOTE: Wireguards only available with Back Mount.



SPECIFICATIONS

CONSTRUCTION

- Injection-molded reflector ensures easy installation, maintenance, and even illumination.
- Heavy-duty, three-piece die-cast aluminum housing with a removable front stencil and light seal.
- Sleek 2.5" profile with softened corners and chamfered edges.
- Optional polycarbonate face shield, tamper-proof screws, swivel pendant, and specialty mounts.

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- NFPA type, universal field selectable chevrons.

VIEWING DISTANCE

- 100 foot visibility rating

CANOPY

- Low-profile universal canopy with 0.75" cast nipple and locking nuts.

APPROVALS

- UL 924 Listed to 100ft Visibility Distance
- CSA C22.2 No. 141-10
- CEC Title 20 Compliant
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA
- BAA Compliant

WARRANTY

- Isolite offers a lifetime warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

