

LPX

Extruded Aluminum LED Exit Sign

DATE:

PROJECT

COMMENTS:



FEATURES

- Attractive, contemporary housing design
- Energy efficient high output LEDs
- As low as 1.1W power consumption
- Black or white baked powder coat
- Swivel pendant Mounting available upon request
- Face-plates slide out for quick and easy installations
- Self-Test/Self-Diagnostic monitoring available
- Maintenance-free nickel cadmium battery
- Short circuit battery protection
- Brownout detection ensures emergency operation during periods of low line voltage
- Line latch prevents unnecessary discharge of battery during installation — loads will not illuminate until after application of utility power
- Key hole Mounting slots and conduit knockouts offer additional Mounting options
- 120/277 VAC field selectable inputs (with the exception of the C1/C2 (Dual Circuit) option which requires voltage specification upon ordering)

CEC Title 20



ORDERING INFORMATION *LPX-AC-G-1-BA-MB*

1. SERIES

LPX

2. OPERATION

AC AC Only
EM Ni-Cad Battery Backup

3. ILLUMINATION

G Green
R Red

4. FACE COUNT

1 Single
2 Double
U Universal

5. FRAME COLOR

BA Brushed Aluminum
BK Black
CC Custom Color
WH White

6. MOUNTING

MB Back Mount
MTEBP Universal Mount
MPAB 12" Swivel Mount (Black)
MPABA 12" Swivel Mount (Brushed Aluminum)
MPAW 12" Swivel Mount (White)

7. OPTIONS

BLANK = NO OPTION
C1 Dual Circuit - 120 VAC
C2 Dual Circuit - 277 VAC
SD Self-Diagnostics (EM Only)
EB Extended Run-time (EM Only)
CW Custom Wording
AA Audible Alarm
FL Flasher
FA Fire Alarm Interface
TP Tamper proof Screws

ACCESSORIES; ORDER SEPARATELY

- WG 2 = Wire guard 14.0" X 10.0" X 4.5"
- WG 3 = Wire guard 14.5" X 6.0" X 10.5"
- WG 10 = Wire guard 13.5" X 12.0" X 16.5"

CONSTRUCTION

- Durable, extruded aluminum

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- NFPA-Type, universal field selectable chevrons

WEIGHT

- AC: 4.75 lbs.
- EM: 5.25 lbs.

TEMPERATURE RATING

- From 50°F to 104°F

APPROVALS

- CSA-US listed
- CEC Title 20 Compliant
- Meets or exceeds UL 924 standards
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA

WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

