

LPX

Extruded Aluminum LED Exit Sign

DATE:

PROJECT

COMMENTS:



FEATURES

- Attractive and contemporary aluminum housing design.
- Energy efficient LEDs with high output.
- Power consumption reaches as low as 1.1W.
- Swivel pendant mounting available upon request.
- Face-plates slide out for quick and easy installations.
- Self-Test/Self-Diagnostic monitoring is available.
- Maintenance free Ni-Cad batteries with short circuit protection.
- Brownout detection ensures emergency operation during periods of low line voltage.
- Line-latch prevents unnecessary discharge of battery during installation. Loads will not illuminate until after application of utility power.
- Key hole mounting slots and conduit knockouts offer additional mounting options.
- 120/277 VAC with field selectable inputs (with the exception of the C1/C2 (Dual Circuit) option which requires voltage specification upon ordering).
- Standard universal face count allows for single or double face applications.



ORDERING INFORMATION *LPX-AC-G-U-BA-MB*

1. SERIES

LPX

2. OPERATION

AC AC Only
EM Ni-Cad Battery Backup

3. ILLUMINATION

G Green
R Red

4. FACE COUNT

U

U Universal

5. FRAME COLOR

BA Brushed Aluminum
BK Black
CC Custom Color
WH White

6. MOUNTING

MTEBP Universal Mount
MPAB 12" Swivel Mount (Black)
MPABA 12" Swivel Mount (Brushed Aluminum)
MPAW 12" Swivel Mount (White)

7. OPTIONS

BLANK = NO OPTION
C1 Dual Circuit - 120 VAC¹
C2 Dual Circuit - 277 VAC¹
SD Self-Diagnostics (EM Only)
EB Extended Run-time (EM Only)

CW Custom Wording
FL Flasher
FA Fire Alarm Interface
TP Tamper proof Screws

ORDERING NOTES

1. This dual circuit option should only be used for exits which are intended to be connected simultaneously to normal and emergency power circuits, but cannot support two hot inputs. Only one of the normal or emergency circuits can be powered at any given time. Energizing both normal and emergency circuits simultaneously will result in damage to the exit sign.
2. Back mount not compatible with two faced units.

ACCESSORIES; ORDER SEPARATELY

- **WG-16.5LX14.0WX3.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 3"
- **WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- **WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- **WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

NOTE: Wireguards only available with Back Mount.



SPECIFICATIONS

CONSTRUCTION

- Durable, extruded aluminum

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- NFPA-type, universal field selectable chevrons.

WEIGHT

- **AC:** 4.75 lbs
- **EM:** 5.25 lbs

TEMPERATURE RATING

- From 50°F to 113°F

APPROVALS

- CSA-US listed
- CEC Title 20 Compliant
- Meets or exceeds UL 924 standards
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA
- BAA Compliant

WARRANTY

Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

