

## LPX-CT

Extruded Aluminum LED Exit Sign with Mobility Symbol

DATE:

COMMENTS:

PROJECT



### FEATURES

- Complies with the State of Connecticut Building Code requirements and provides an EXIT sign with a 6.0" International Symbol of Accessibility
- Universal Mounting pattern is stamped into the back plate for easy surface Mounting to a J-box
- Long life nickel cadmium Maintenance-free battery provides required 90 minutes of emergency operation
- Electronic Control Circuit and Isolation Transformer provide current control and circuit protection, ensuring optimum LED efficiency and life
- Solid-state transfer relay ensures reliability — no relay contacts to oxidize and fail
- High-output, energy efficient LED technology
- Line latch prevents unnecessary discharge of battery
- Brownout detection ensures emergency operation during periods of low line voltage
- LED AC indicator and push-to-test switch
- 120/277 VAC field selectable inputs



### ORDERING INFORMATION *LPX-CT-AC-B-1-BA-MB*

1. SERIES	2. OPERATION	3. ILLUMINATION	4. FACE COUNT	5. FRAME COLOR
LPX-CT	-	-	-	-
	<b>AC</b> AC Only <b>EM</b> Ni-Cad Battery Backup	<b>G</b> Green <b>R</b> Red	<b>1</b> Single <b>2</b> Double <b>U</b> Universal	<b>BA</b> Brushed Aluminum <b>BK</b> Black <b>WH</b> White
6. MOUNTING	7. OPTIONS			
<b>MB</b> Back Mount <b>MTEBP</b> Universal Mount <b>MPAB</b> 12" Swivel Mount (Black) <b>MPABA</b> 12" Swivel Mount (Brushed Aluminum) <b>MPAW</b> 12" Swivel Mount (White)	<b>BLANK = NO OPTION</b> <b>C1</b> Dual Circuit - 120 VAC <b>C2</b> Dual Circuit - 277 VAC <b>EB</b> Extended Run-time (EM Only) <b>AA</b> Audible Alarm <b>FL</b> Flasher			

### ACCESSORIES; ORDER SEPARATELY

- WG 2 = Wire guard 14.0" X 10.0" X 4.5"
- WG 3 = Wire guard 14.5" X 6.0" X 10.5"
- WG 10 = Wire guard 13.5" X 12.0" X 16.5"

**CONSTRUCTION**

- Durable, extruded aluminum

**LETTERS**

- 6.0" high; 0.75" stroke

**ARROWS**

- NFPA-Type, universal field selectable chevrons

**WEIGHT**

- AC: 4.7 lbs.
- EM: 5.2 lbs.

**TEMPERATURE RATING**

- From 50°F to 113°F

**APPROVALS**

- CSA-US listed
- UL 924
- State of Connecticut Building Code Paragraph 1011.1.2
- NFPA 101 Life Safety Code
- NFPA 70 - NEC
- OSHA
- NAFTA

**WARRANTY**

Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.

**DIMENSIONS**