

LED Low Level Recessed Emergency Light

COMMENTS:

PROJECT

.

DATE:

FEATURES

- More effective in illuminating the path of egress than traditional ceiling or wall mounted emergency lights.
- Fully self-contained emergency light that can be recessed into walls.
- UL listed for a minimum run-time of 90 minutes.
- Tamper resistant design with no visible mounting hardware.
- Universal back box can be pre-shipped for pre-installation at job-site.
 - Can be painted or wallpapered to seamlessly blend with architecture.
- Uses three high-output white LEDs with just 11 Watts of total load and an output of 311 lumens.
- Up to 50.0' on center spacing in a 4' wide path of egress.
 - Optional infrared hand-held remote control testing can be ordered separately.
- Modular assembly and quick connector wiring.
- Line latch prevents unnecessary discharge of battery during installation.
- Brownout sensing ensures emergency operation during periods of low line voltage.
- Low voltage cut-off prevents battery damage and ensures positive charge acceptance following an extended discharge.
- Fully automatic operation.
- Battery diagnostics come standard on all units.
- Soft start, solid state, microprocessor controlled circuitry for soft close doors.
- 120/277 VAC with field selectable inputs.

ORDERING INFORMATION LTP-LC-MR

CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS

Only available with Adobe Acrobat and Acrobat Reader

1. SERIES	2. BATTERY	3. MOUNTING	4. OPTIONS
LTP		-	-
	LCLead Calcium Battery BackupNCNi-Cad Battery Backup	MRLBRecessed Mount, Less Back Box1MRRecessed Mount	BLANK = NO OPTION CC Custom Color TD Time Delay - 120/277 VAC (15 min.)

ORDERING NOTES

1. Must order LTP-ACCY-RBB separately

ACCESSORIES; ORDER SEPARATELY

- TLRT = Infrared Remote Control
- LTP-ACCY-RBB = Recessed Backbox for LTP



SPECIFICATIONS

CONSTRUCTION

- Textured, white powder coated, die-cast zinc frame and door
- Spring latch lamp holders
- No external mounting hardware

WEIGHT

8 lbs


APPROVALS

- UL 924
- NY City approved calendar #48850
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA
- CEC Title 20 Compliant

WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.

DIMENSIONS



ISOLITE • WWW.ISOLITE.COM ISOLITE HEADQUARTERS • 800.888.5483 • 31 WATERLOO AVENUE, BERWYN, PA 19312 ISOLITE WEST • 800.799.5343 • 3563 SUELDO, SUITE M, SAN LUIS OBISPO, CA 93401

