



LTP

LED Low Level Recessed Emergency Light

DATE:

PROJECT

COMMENTS:

FEATURES

- More effective in illuminating the path of egress than traditional ceiling or wall mounted emergency lights
- Fully self-contained emergency light that can be recessed into walls
- 2 Hour standard run-time
- Tamper resistant design — no visible mounting hardware
- Universal back box can be pre-shipped for pre-installation at job-site
- Can be painted or wallpapered to seamlessly blend with architecture
- Uses three high-output white LEDs with just 11 Watts of total load
- Up to 50.0' on center spacing over a 4.0' path of egress
- Soft close doors
- Optional infrared hand-held remote control testing
- Modular assembly and quick connector wiring
- Solid-state, microprocessor controlled circuitry
- Line latch prevents unnecessary discharge of battery during installation
- Brownout sensing ensures emergency operation during periods of low line voltage
- Battery LVCO
- Fully automatic operation
- Battery diagnostics come standard on all units
- Soft start lamp circuit
- 120/277 VAC field selectable inputs



ORDERING INFORMATION *LTP-LC-MRLB*

1. SERIES

LTP

2. BATTERY

LC Lead Calcium Battery Backup
NC Ni-Cad Battery Backup

3. MOUNTING

MRLB Recessed Mount, Less Back box
MR Recessed Mount

4. OPTIONS

BLANK = NO OPTION
CC Custom Color
TD Time Delay - 120/277 VAC (15 min.)

ACCESSORIES; ORDER SEPARATELY

- TLRT = Infrared Remote Control
- LTP-ACCY-RBB = Recessed Backbox for LTP

CONSTRUCTION

- Textured, white powder coated, die-cast zinc frame and door
- Spring latch lamp holders
- No external Mounting hardware

WEIGHT

- 8 lbs.

APPROVALS

- UL924
- NY City approved calendar #48850
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA

TEMPERATURE RATING

- LC: From 45°F to 85°F
- NC: From 32°F to 102°F

WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.

DIMENSIONS

