



LTP

LED Low Level Recessed Emergency Light

DATE:

PROJECT

COMMENTS:

FEATURES

- This innovative emergency light mounts just 18 inches above the floor and illuminates for up to 50ft center-to-center spacing.
- More effective in illuminating the path of egress than traditional ceiling or wall mounted emergency lights.
- Fully self-contained emergency light that can be recessed into walls.
- UL listed for a minimum run-time of 2 hours.
- Tamper resistant design with no visible mounting hardware.
- Universal back box can be pre-shipped for pre-installation at job-site.
- Can be painted or wallpapered to seamlessly blend with architecture.
- Uses three high-output white LEDs with just 11 Watts of total load and an output of 311 lumens.
- Up to 50.0' on center spacing in a 4' wide path of egress.
- Optional infrared hand-held remote control testing can be ordered separately.
- Modular assembly and quick connector wiring.
- Line latch prevents unnecessary discharge of battery during installation.
- Brownout sensing ensures emergency operation during periods of low line voltage.
- Low voltage cut-off prevents battery damage and ensures positive charge acceptance following an extended discharge.
- Fully automatic operation.
- Battery diagnostics come standard on all units.
- Soft start, solid state, microprocessor controlled circuitry for soft close doors.
- 120/277 VAC with field selectable inputs.



ORDERING INFORMATION *LTP-LC-MR*

1. SERIES

LTP

2. BATTERY

LC Lead Calcium Battery Backup
NC Ni-Cad Battery Backup

3. MOUNTING

MRLB Recessed Mount, Less Back Box¹
MR Recessed Mount

4. OPTIONS

BLANK = NO OPTION
CC Custom Color
TD Time Delay - 120/277 VAC (15 min.)

ORDERING NOTES

- 1. Must order LTP-ACCY-RBB separately.

ACCESSORIES; ORDER SEPARATELY

- **TLRT** = Infrared Remote Control
- **LTP-ACCY-RBB** = Recessed Backbox for LTP

SPECIFICATIONS

CONSTRUCTION

- Textured, white powder coated, die-cast zinc frame and door
- Spring latch lamp holders
- No external mounting hardware

WEIGHT

- 8 lbs

APPROVALS

- UL 924
- NY City approved calendar #48850
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA
- CEC Title 20 Compliant
- BAA Compliant

WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.



DIMENSIONS

