

MAX-E

Wet Location Emergency Light

DATE:	COMMENTS:
PROJECT	

Product Discontinued.



FEATURES

- IP66 rated, suitable for NEMA 4X applications
- Designed to stand up to abuse in applications such as schools, institutions, public areas and apartment complexes where vandalism may occur
- Two bottom mounted MR16 style lamps
- Sealed External Momentary test switch and dual diagnostic LED indicator display AC presence and Hi-Charge status
- Maintenance-free sealed nickel cadmium batteries provide a minimum of 90 minutes of emergency run-time
- Line latch prevents unnecessary discharge of battery during installation loads will
 not illuminate until after application of utility power
- Short circuit battery protection
- Brownout detection ensures emergency operation during periods of low line voltage
- 120/277 VAC field selectable inputs
- BAA Compliant







ORDERING INFORMATION *MAX-E-12V42W-BK-MB-L65*

1. SERIES	2. OPERATION	3. FRAME COLOR	4. MOUNTING		4. LAMP SOURCE ¹	
MAX-E	-	-	-		-	-
	12V42W 12 Volts, 42 Watts 12V90W 12 Volt, 90 Watts 6V42W 6 Volts, 42 Watts	BK Black WH White	MB ME MTEB MPAB MPABA MPAW	Back Mount End Mount/Side Mount Top/End/Back Mount 12" Swivel Mount (Black) 12" Pendant Mount (Brushed Aluminum) 12" Swivel Mount (White)	L65 LED 6V 5W L67 LED 6V 7W L122 LED 12V 2W L125 LED 12V 5W L127 LED 12V 7W	

5. OPTIONS

BLANK = NO OPTION SD Self Diagnostics (EM Only)

ORDERING NOTES

 Additional lamp options may be available, please contact Quotes@Isolite.com if non-LED lamps are required.

ACCESSORIES; ORDER SEPARATELY

WG 5 = Wire guard 15.75" X 14.75" X 6.75"



MAX-E

Wet Location Emergency Light







CONSTRUCTION

- Heavy-duty 0.420" cast aluminum
- Lamp housing constructed of vandal resistant polycarbonate
- Durable white or black powder-coat finish

TEMPERATURE RATING

• From 50°F to 104°F

APPROVALS

- CSA-US listed
- Meets or exceeds UL 924 standards
- IP66
- NFPA 101 Life Safety Code
- NFPA 70 NEC
- OSHA
- BAA Compliant

WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS



