

DATE:	COMMENTS:
PROJECT:	

FEATURES



- Very low profile extruded aluminum housing and mount bracket blend seamlessly with structural metal frames
- Remote power supply for 10W and 20W EM and AC model single fixtures
- Certified IP66 housing withstands multi direction water spray and fine dust ingress
- Universal side or top mount
- Wide lighting distribution designed for entrance walkways
- 10W or 20W emergency power models
- Option for 20W models to operate for 2 hours in emergency mode
- Standard CCT 5000K, with 2900K, 3200K and 3800K options available



ORDERING INFORMATION *ODLM-10-AC-BA-MBB*

1. SERIES	2. VA RATING	3. OPERATION	4. HOUSING COLOR
ODLM	-	-	-
	10 10 Watt 20 20 Watt	AC AC Only EM Battery Backup	BA Brushed Aluminum WH White BK Black
5. MOUNTING	6. OPTIONS		
MMB	-		
MMB Mullion Mount Back	BLANK = NO OPTION SD Self-Diagnostics C1 Dual Circuit (120V) C2 Dual Circuit (277V) EB 2 Hour Runtime 2900K 2900K Lens Filter 3200K 3200K Lens Filter 3800K 3800K Lens Filter		

CONSTRUCTION

- Extruded aluminum lamp housing 2" diameter, with gasketed mount bracket only
- Waterproof compression seal for universal wall or top mount
- Gasketed, molded end caps and sealed acrylic lens
- Stainless steel hardware

ELECTRONICS

- Line latch circuit prevents unwanted emergency activation at installation.
- Low Voltage Disconnect prevents deep battery discharge

TEMPERATURE RATING

- **EM:** Backup Battery: -4°F to 104°F
- **AC:** No Backup Battery: -4°F to 104°F

APPROVALS

- UL 924
- NFPA 101 Life Safety Code
- IP66


WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.

MOUNTING DIMENSIONS


Remote Power Supply

10W AC & EM Models



Remote Power Supply

20W AC & EM Models



MAXIMUM WIRING LENGTH FROM POWER SUPPLY TO FIXTURE		
WIRING SIZE AWG	LENGTH (FT)	LENGTH (FT)
	10W UNIT	20W UNIT
#22		20
#20	12	40
#18	25	60
#16	50	100
#14	75	160
#12	125	250