



PH

Aluminum Frame Photoluminescent Exit Sign

DATE:

PROJECT:

COMMENTS:

FEATURES

- Activation requires only 5 foot-candles (54 lux) of unfiltered fluorescent light for 60 minutes (must be externally illuminated during normal building occupation)
- Concealed mounting hardware for surface mounted units
- Standard universal mounting canopy
- 50.0' viewing distance
- Chain and swivel pendant mounts available
- Non-electrical
- Easy and fast installation
- Maintenance-free
- No expiration date
- Suitable for indoor or outdoor applications



ORDERING INFORMATION PH-G-1-BA-MB

1. SERIES	2. LEGEND COLOR	3. FACE COUNT	4. HOUSING COLOR	5. MOUNTING	6. OPTIONS
PH	-	-	-	-	-
	G Green R Red	1 Single 2 Double	BA Brushed Aluminum BK Black WH White	MB Back Mount MTEB Top/End/Back Mount MC Chain Mount MPA 12" Pendant Mount MPB 24" Pendant Mount MPC 36" Pendant Mount MPD 48" Pendant Mount	BLANK = NO OPTION VR1 Vandal Resistant Shield (Incl. TP) VR2 Vandal Resistant Shield (Incl. TP)

NOTES

1. Includes Tamperproof Screws

ACCESSORIES; ORDER SEPARATELY

- WG 2 = Wire guard 14.0" X 10.0" X 4.5"
- WG 3 = Wire guard 14.5" X 6.0" X 10.5"
- WG 10 = Wire guard 13.5" X 12.0" X 16.5"

CONSTRUCTION

- Extruded aluminum frame
- Strontium oxide aluminate photoluminescent pigment molded into a rigid flame/fire-resistant PVC sheet

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- NFPA-Type, universal, field installable, self-adhesive chevrons

DIMENSIONS

- 14.5" X 9.31"

WEIGHT

- 3.5 lbs.

APPROVALS

- UL 924
- NFPA 101 Life Safety Code
- NFPA 70 - NEC
- OSHA

WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

