



PH100

Photoluminescent Exit Sign

DATE:

PROJECT:

COMMENTS:



FEATURES

- Activation requires only 5 foot-candles (54 lux) of unfiltered fluorescent or LED light for 60 minutes (must be externally illuminated during normal building occupation).
- The photoluminescent material allows for a 100' viewing distance.
- Suitable for use in indoor, outdoor, wet, and hazardous locations.
- The life expectancy is 25+ years.
- Universal, field installed chevrons are universal and field installable.
- No electrical connections are needed for operation.
- Installation is fast, easy, and maintenance free.



ORDERING INFORMATION *PH100-1-BK-MTEB*

1. SERIES	2. FACE COUNT	3. FACE COLOR	4. MOUNTING
PH100	-	-	MTEB
	1 Single 2 Double	BK Black G Green R Red	MTEB Top/End/Back Mount

ACCESSORIES; ORDER SEPARATELY

- **WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- **WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

NOTE: Wireguards only available with Back Mount.

SPECIFICATIONS

CONSTRUCTION

- Durable ABS background panel is available in red, green, or black, with standard photoluminescent letters.

TEMPERATURE RATING

- From -20°F to 150°F (-28°C to 65°C)

APPROVALS

- UL 924
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA
- BAA Compliant

WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.



DIMENSIONS

