

# PH100

Photoluminescent Exit Sign

DATE:

PROJECT:

COMMENTS:



## FEATURES

- Activation requires only 5 foot-candles (54 lux) of unfiltered fluorescent or LED light for 60 minutes (must be externally illuminated during normal building occupation)
- 100.0' viewing distance
- Suitable for hazardous locations
- Approved for outdoor and wet locations
- 25+ year life expectancy
- Maintenance-free
- Universal, field installed chevrons
- Non-electrical
- Fast, easy installation



## ORDERING INFORMATION *PH100-1-BK-MTEB*

### 1. SERIES

PH100

### 2. FACE COUNT

-

- 1 Single
- 2 Double

### 3. FACE COLOR

-

- BK** Black
- G** Green
- R** Red

### 4. MOUNTING

MTEB

MTEB Top/End/Back Mount

## ACCESSORIES; ORDER SEPARATELY

- WG 10 = Wireguard 13.5" X 12.0" X 16.5"



**CONSTRUCTION**

- Durable ABS background panel available in red, green, or black, with photoluminescent letters

**APPROVALS**

- UL 924
- NFPA 101 Life Safety Code
- NFPA 70 - NEC
- OSHA

**WARRANTY**

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

**DIMENSIONS**

