

DATE:	COMMENTS:
PROJECT:	



FEATURES

- Activation requires only 5 foot-candles (54 lux) of LED or unfiltered fluorescent light for 60 minutes (must be externally illuminated during normal building occupation).
- Universal mounting is standard.
- No electrical connections are needed for operation.
- Installation is fast, easy, and maintenance free.
- The strontium oxide aluminate photoluminescent pigment allows for a 50' viewing distance with no expiration date.



ORDERING INFORMATION *PHL-G-1-BK-MB*

1. SERIES	2. ILLUMINATION	3. FACE COUNT	4. FRAME COLOR	5. MOUNTING
PHL	-	1	BK	MB
	G Green R Red	1 Single	BK Black	MB Back Mount

ACCESSORIES; ORDER SEPARATELY

- WG-16.5LX14.0WX3.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 3"
- WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

NOTE: Wireguards only available with Back Mount.

SPECIFICATIONS

CONSTRUCTION

- Thermoplastic frame
- Strontium oxide aluminate photoluminescent pigment molded into a rigid fire/flame-resistant PVC sheet.

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- NFPA-type, universal, field installable, self-adhesive chevron.

WEIGHT

- 14 lbs

TEMPERATURE RATING

- From 50°F to 104°F (10°C to 40°C)

APPROVALS

- UL 924
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA
- BAA Compliant

WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.



DIMENSIONS

