

PHL

Thermoplastic Photoluminescent Exit Sign

DATE:

COMMENTS:

PROJECT:

FEATURES

- Activation requires only 5 foot-candles (54 lux) of unfiltered fluorescent light for 60 minutes (must be externally illuminated during normal building occupation)
- Standard universal wall mounting
- Non-electrical
- Fast, easy installation
- Maintenance-free
- No expiration date



ORDERING INFORMATION *PHL-G-1-BK-MB*

1. SERIES	2. ILLUMINATION	3. FACE COUNT	4. FRAME COLOR	5. MOUNTING
PHL	-	- 1	- BK	- MB
	G Green R Red	1 Single	BK Black	MB Back Mount

ACCESSORIES; ORDER SEPARATELY

- WG 2 = Wire guard 14.0" X 10.0" X 4.5"
- WG 10 = Wireguard 13.5" X 12.0" X 16.5"

SPECIFICATIONS

CONSTRUCTION

- Thermoplastic frame
- Strontium oxide aluminate photoluminescent pigment molded into a rigid fire/flame-resistant PVC sheet

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- NFPA-Type, universal, field installable, self-adhesive chevron

APPROVALS

- UL 924
- NFPA 101 Life Safety Code
- NFPA 70 - NEC
- OSHA s

WEIGHT

- 14.0 lbs.

WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

