

DATE:	COMMENTS:
PROJECT:	

FEATURES

- Activation requires only 5 foot-candles (54 lux) of unfiltered fluorescent, LED, metal halide, or mercury vapor lighting for 60 minutes (must be externally illuminated during normal building occupation)
- PH100 tested and listed per UL924 requirements for use with LED lighting
- 100.0' viewing distance
- Suitable for hazardous locations
- Approved for damp locations
- 25+ year life expectancy
- Maintenance-free
- Universal, field installed chevrons
- Non-electrical
- Fast, easy installation



ORDERING INFORMATION *PHP100-1-WH-MTEB*

1. SERIES	2. FACE COUNT	3. FRAME COLOR	4. MOUNTING
PHP100	-	WH	MTEB
	1 Single 2 Double	WH White	MTEB Top/End/Back Mount

ACCESSORIES; ORDER SEPARATELY

- WG 2 = Wire guard 14.0" X 10.0" X 4.5"
- WG 3 = Wire guard 14.5" X 6.0" X 10.5"
- WG 10 = Wire guard 13.5" X 12.0" X 16.5"

SPECIFICATIONS

CONSTRUCTION

- Durable ABS panel

APPROVALS

- UL 924
- NFPA 101 Life Safety Code
- NFPA 70 - NEC
- OSHA

WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

