

## RLC-LED

Thermoplastic Exit & Emergency Combo

DATE:

COMMENTS:

PROJECT



### FEATURES

- Suitable for use in damp locations
- Ultra-bright, energy efficient, long-life red or green LED
- Two, fully adjustable, high performance, premium grade, ultra-bright white LED emergency lamps
- Heads produce 125 Lumens for optimum spacing and distribution
- Remote capability is standard and can operate two 1W LED lamp-heads, or can be used for longer run-time
- Compatible with Isolite MVH and MVI remote heads
- Output voltage 3.6V needed to power remote heads
- Provides 90 minutes of emergency operation
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- Maintenance-free nickel cadmium batteries
- Available with full self-diagnostic option
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates recharge of a discharged battery in 24 hours
- 120/277 VAC field-selectable inputs



### ORDERING INFORMATION *RLC-LED-G-U-BK-MTEB*

1. SERIES	2. ILLUMINATION	3. FACE COUNT	4. FRAME COLOR	5. MOUNTING	6. OPTIONS
RLC-LED	-	U	-	MTEB	-
	R Red G Green	U Universal	BK Black WH White	MTEB Top/End/Back Mount	BLANK = NO OPTION SD Self-Diagnostics

#### ORDERING NOTES

1. Black finish only available with SD units

#### ACCESSORIES; ORDER SEPARATELY

- WG 5 = Wire guard 15.75" X 14.75" X 6.75"
- WG 10 = Wire guard 13.5" X 12.0" X 16.5"



## CONSTRUCTION

- High-impact, thermoplastic housing

## ARROWS

- Field selectable knockout chevron directional indicators

## TEMPERATURE RATING

- From 50°F to 104°F

## APPROVALS

- UL 924
- UL 924 damp location
- NFPA Life Safety Code 101
- NFPA 70 - NEC
- OSHA

## WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.

## DIMENSIONS

