

DATE:

COMMENTS:

PROJECT:

FEATURES



- Suitable for wet location applications.
- Super-bright LEDs with long life expectancy.
- Quick-connect components and snap-on canopy for easy installation.
- Nickel cadmium battery provides a minimum of 90 minute emergency operation.
- Sealed external momentary test switch and dual diagnostic LED indicator displays AC presence and Hi-Charge status.
- Self-Test / Self-Diagnostic monitoring is available.
- Low voltage cut-off prevents battery damage and ensures positive charge acceptance following an extended discharge.
- Line-latch prevents unnecessary discharge of battery during installation. Loads will not illuminate until after application of utility power.
- 120/277 VAC with field selectable inputs (with the exception of the C1/C2 (dual circuit) option which requires voltage specification upon ordering).



ORDERING INFORMATION *RWL-AC-G-1-BK-MTEBP*

1. SERIES	2. OPERATION	3. ILLUMINATION	4. FACE COUNT	5. FRAME COLOR
RWL	- -	-	-	-
	AC AC Only EM Ni-Cad Battery Backup	G Green R Red	1 Single 2 Double	BK Black GY Gray WH White
6. MOUNTING	7. OPTIONS			
MTEBP	-			
MTEBP Universal Mount	BLANK = NO OPTION C1 Dual Circuit - 120 VAC (AC Only) ¹ C2 Dual Circuit - 277 VAC (AC Only) ¹	SD Self-Diagnostics (EM Only) TP Tamperproof Screws		

ORDERING NOTES

1. This dual circuit option should only be used for exits which are intended to be connected simultaneously to normal and emergency power circuits, but cannot support two hot inputs. Only one of the normal or emergency circuits can be powered at any given time. Energizing both normal and emergency circuits simultaneously will result in damage to the exit sign.

ACCESSORIES; ORDER SEPARATELY

- **WG-16.5LX14.0WX3.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 3"
- **WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- **WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- **WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

NOTE: Wireguards only available with Back Mount.

SPECIFICATIONS
CONSTRUCTION

- 5VA flame retardant
- UV Stabilized Polycarbonate housing
- High-impact resistant polycarbonate lens
- Corrosion resistant enclosure
- Knockouts provided for conduit feed applications

ELECTRICAL

- **Input Power:** 3.4W Max

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- NFPA-type, field selectable chevrons

WEIGHT

- 4 lbs

TEMPERATURE RATING

- From -4°F to 122°F

APPROVALS

- UL 924 Listed for Wet Location
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA
- CEC Title 20 Compliant

WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS
